

Numerics

802.1p

QoS priority 2-14, 13-5

A

AARP 12-4

Abdication

VRRP 9-16

ABR 6-2

displaying information 6-48

OSPF 6-2

Access Control List. See ACL.

Access policy 5-22, B-7, B-9

ACL

AS-path 8-43

BGP4

AS-path 8-43

community 8-49

community 8-49

IP 3-1

IPX/SAP 11-9

Active router

SRP 10-3, 10-10

Address

AppleTalk 12-5

IP 5-4

BootP/DHCP 5-36

virtual router 9-4

IPX 11-3

MAC

virtual router 9-3

Administrative distance 5-40, 6-36, 8-28

Advertisement

BGP4

neighbor 8-14

route summarization 8-30

DVMRP 7-39

IP/RIP default route 5-41

IPX/RIP 11-14

packet size 11-13

IPX/SAP 11-14

ACL 11-9

packet size 11-13

OSPF 6-1

area 6-7

maximum 6-34

retransmit interval 6-17, 6-22

RIP 5-2

VRRP suppression 9-5, 9-13

VRRP 9-4

AEP 12-3

Age

ARP

AppleTalk 12-17

IP 5-7

IPX routes 11-15

IPX/SAP 11-15

OSPF

LSA 6-44

Alarm

RMON Group 3 A-3

AppleTalk

address 12-5

ARP

age 12-17

retransmit count 12-17

retransmit interval 12-18

clearing statistics 12-21

configuring 12-1

displaying information 12-20

enabling 12-4, 12-7, 12-8

glean 12-18

network filter 12-3, 12-13, B-20

overview 12-1

parameters 12-16

RTMP update interval 12-19

statistics 12-20

VLAN 12-13, 13-3, 13-20

- ZIP query interval 12-19
 - zone 12-5
 - filter 12-2, B-20
 - zone filter 12-10
- AppleTalk Cable VLAN
 - dynamic port add 13-32
- AppleTalk cable VLAN 13-1, 13-29
 - configuring 13-43
- AppleTalk router 12-7
- AppleTalk socket
 - QoS priority 2-25
- Area
 - OSPF 6-2
 - assigning to interface 6-14
 - configuring 6-7
 - displaying information 6-40
- Area range
 - OSPF 6-2
 - configuring 6-13
- ARP 13-36
 - age
 - AppleTalk 12-17
 - IP 5-7
 - IP
 - Host unreachable message 5-3
 - proxy 5-11
 - retransmit count
 - AppleTalk 12-17
 - retransmit interval
 - AppleTalk 12-18
 - static entry 5-20
- ARP cache
 - IP/RIP
 - displaying 5-49
- ASBR 6-2
 - displaying information 6-48
- AS-path length 8-3
- Assigning
 - IP address 5-4
- ATP 12-3
- Attribute entries
 - BGP4
 - maximum 8-23
 - displaying 8-90
 - summary 8-76
- Authentication
 - VRRP 9-5, 9-12
- Autonomous system
 - BGP4 8-1
 - OSPF 6-1
- B**
- Backup
 - VRRP 9-13
 - abdication 9-16
 - preempt 9-15
 - priority 9-13
- BGP4
 - administrative distance 8-28
 - AS-path ACL 8-43
 - AS-path filter 8-41, B-23
 - attribute entries
 - maximum 8-23
 - autonomous system 8-1
 - clearing diagnostic buffers 8-96
 - clearing route flap dampening statistics 8-73, 8-75, 8-94
 - clearing traffic counters 8-94
 - community ACL 8-49
 - community filter 8-47, B-24
 - confederation 8-33
 - configuring 8-1
 - dampening 8-64
 - default information originate 8-27
 - default local preference 8-26
 - displaying information 8-76
 - IP route table 8-92
 - neighbor 8-79
 - route 8-87
 - route attributes 8-90
 - route flap dampening 8-92
 - summary 8-76
 - displaying route dampening statistics 8-74
 - distribute list 8-53
 - enabling 8-11
 - fast external fallover 8-20
 - flap dampening 8-64
 - hold time 8-20
 - IP address filter 8-40, B-22
 - IP prefix list 8-50
 - IP Route Table 6-1, 8-1
 - keepalive 8-5
 - changing 8-20
 - load sharing 8-24
 - local AS 8-12
 - memory 8-10
 - messages 8-4
 - Multi-Exit Discriminator 8-27, 8-29
 - neighbor 8-14
 - distribute list 8-53
 - maximum 8-21
 - resetting session 8-95
 - network advertising 8-25
 - parameters 8-6
 - redistribution 8-37, B-27
 - regular expressions 8-44
 - route
 - aggregation 8-35
 - flap dampening 8-64
 - map 8-55
 - maximum 8-22
 - reflection 8-31
 - summarization 8-30
 - synchronization 8-30
 - table 8-2
 - route table
 - path selection 8-3
 - table map 8-63

- un-suppressing a route 8-95

BootP

- hops 5-7
- IP address stamp 5-36

Broadcast

- directed 5-9
- filter B-13
- IP 5-12
- leaks 13-10

BSR 7-13

- displaying 7-21

C

Cable

- AppleTalk range 12-5
- AppleTalk VLAN 13-29

Cache

- ARP
 - displaying 5-49
- IP forwarding
 - displaying 5-53
- IP host
 - displaying 5-50
- IPX 11-19
- PIM-SM 7-27

CIDR 5-4, 5-14

Confederation 8-33

Configuring

- AppleTalk 12-1
- AppleTalk cable VLAN 13-29
- BGP4 8-1
- DVMRP 7-32
- IGMP 7-2
- IP and IP/RIP 5-3
- IP multicast 7-1
- IP tunnel 7-41
- IP/RIP 5-1
- IPX 11-1
- OSPF 6-1
- PIM-DM 7-7
- PIM-SM 7-14
- port-based VLAN 13-13, 13-17
- protocol VLAN
 - dynamic ports 13-32
 - static ports 13-13
- SRP 10-1, 10-2
- static route
 - IP multicast 7-42
- VRRP 9-1, 9-2

Conventions

- manual 1-1

Counters

- BGP4
 - clearing 8-94

D

DDP 12-4

Dead interval

SRP 10-11

VRRP 9-14

DECnet

VLAN 13-3, 13-20

Default gateway

DVMRP 7-38

Default information originate

BGP4 8-27

OSPF 6-32

Default local preference 8-26

Default network route 5-18

Default route

BGP4 8-27

IP/RIP

- advertising and learning 5-41

OSPF 6-32

- stub area 6-7

Default VLAN 13-5, 13-13

DHCP

- IP address stamp 5-36

Directed broadcasts 5-9

Distance

BGP4 8-28

IP/RIP 5-40

OSPF 6-36

Downstream router

- IP multicast 7-1

DR

OSPF 6-3

- election 6-3

DVMRP 7-30

- advertisement 7-39

- default gateway 7-38

- encapsulation 7-40

- graft 7-32

- graft retransmit timer 7-36

- interface parameters 7-38

- metric 7-39

- neighbor timeout 7-34

- probe interval timer 7-37

- prune 7-31

- prune timer 7-36

- report interval timer 7-37

- route discard time 7-35

- route expire timeout 7-35

- trigger interval timer 7-37

- TTL 7-38

Dynamic port 13-9, 13-32

- aging 13-32

E

ELAP 12-4

Enabling

- ACL 3-3

- AppleTalk 12-4

- BGP4 8-11

- DVMRP 7-32

- IP/RIP 5-4

- IPX 11-2
- OSPF 6-7
- PIM-DM 7-7
- PIM-SM 7-15
- SRP on the Router 10-8
- VRRP 9-7
- Encapsulation
 - DVMRP 7-40
 - IP 5-35
- Event
 - RMON Group 9 A-3
- Excluded port
 - VLAN 13-10
- Exit overflow interval
 - OSPF 6-35
- Extended IP ACL 3-6
- External LSA
 - displaying 6-44

F

- Fast external fallover 8-20
- Fast Port Span 4-1
- Fast Uplink Span 4-3
- Filter B-1
 - AppleTalk network 12-3, 12-13, B-20
 - AppleTalk zone 12-2, 12-10, B-20
 - AS-path 8-41, B-23
 - BGP4
 - AS-path 8-41, B-23
 - community 8-47, B-24
 - distribute list 8-53
 - IP address 8-40, B-22
 - redistribution 8-37, B-27
 - broadcast B-13
 - community 8-47, B-24
 - default action B-3
 - distribute list 8-53
 - extended IP ACL 3-6
 - IP access policy 5-22, B-7
 - IP prefix list 8-50
 - IP route B-16
 - IP, by protocol 5-22
 - IP/RIP 5-21
 - displaying 5-62
 - neighbor 5-31
 - redistribution 5-32, B-26
 - route 5-29
 - IP/RIP neighbor B-17
- IPX
 - forward 11-5, B-19
 - GNS replies 11-10
- IPX/RIP 11-7, B-19
- IPX/SAP 11-9, B-20
- MAC address B-12
- MAC address lock B-14
- multicast B-14
- named IP ACL 3-12
- neighbor distribute list 8-53

- OSPF
 - redistribution 6-22, B-27
 - precedence B-4
 - QoS B-5
 - redistribution B-25
 - scope B-2
 - standard IP ACL 3-5
 - TCP/UDP access policy B-9
- Flow cache
 - PIM-SM 7-27
- Forwarding
 - broadcasts 5-12
 - directed broadcasts 5-9
 - source routing 5-13
- Forwarding cache
 - IP/RIP 5-53
 - IPX 11-19
- Frame type
 - IPX 11-1

G

- Gateway
 - DVMRP 7-38
- Getting Help 1-3
- Glean
 - AppleTalk 12-18
- GNS replies
 - disabling 11-11
 - filter 11-10
 - round robin 11-10
- Graft
 - DVMRP 7-32
 - retransmit timer 7-36
 - PIM-DM 7-6
 - retransmit timer 7-10
- Grounding iii
- Group
 - IPX forward filter 11-5, B-19
 - IPX/RIP filter 11-7, B-19
 - IPX/SAP filter 11-9, B-20
 - PIM-SM
 - displaying 7-20
- Group presence
 - IP multicast 7-2

H

- Health check 14-3
- Hello timer
 - PIM-DM 7-9
 - VRRP 9-14
- Help
 - getting 1-3
- Helper
 - UDP 5-41
- History
 - RMON Group 2 A-2
- Hold down 5-2
- Hold time

- BGP4 8-20
- Hop
 - BootP 5-7
 - IP/RIP
 - count limit 5-2
 - IPX
 - count increment 11-12
- Host cache
 - IP/RIP
 - displaying 5-50
- I
- IGMP
 - configuring 7-2
 - maximum response time 7-3
 - membership time 7-3
 - query
 - disabling 7-3
 - query interval 7-2
- Inactivity timer
 - PIM-DM 7-11
- Injection 14-1
- Interface
 - AppleTalk 12-5
 - enabling 12-8
 - DVMRP parameters 7-38
 - IP access policy 5-27
 - IP route filter 5-30
 - IP/RIP 5-34
 - displaying information 5-46
 - enabling 5-37
 - parameters 5-37
 - IPX
 - configuring 11-3
 - displaying information 11-17
 - frame type 11-1
 - parameters 11-2
 - loopback 8-13
 - OSPF
 - blocking LSAs 6-18
 - defaults 6-16
 - displaying information 6-42
 - PIM-DM parameters 7-11
 - PIM-SM parameters 7-15
 - SRP
 - parameters 10-11
 - track port 10-3
 - track port
 - SRP 10-10, 10-14
 - VRRP 9-15
 - track priority
 - VRRP 9-15
 - virtual 13-3, 13-12
 - VLAN 13-8, 13-21
 - VRRP
 - track port 9-5
- Intermediate node
 - IP multicast 7-2
- IP
 - ARP
 - age 5-7
 - static 5-20
 - configuring 5-1
 - configuring IP and IP/RIP 5-3
 - enabling IP/RIP 5-4
 - encapsulation 5-35
 - filtering by protocol 5-22
 - hop 5-1
 - interface parameters, modify 5-34
 - load sharing 5-10
 - maximum number of routes 6-1, 8-1
 - metric 5-36
 - MTU 5-35
 - network mask 5-4
 - precedence
 - filtering 3-8
 - Proxy ARP 5-11
 - RARP
 - static 5-20
 - route table 5-1
 - static route 5-14
 - TCP and UDP ports 5-23
 - TOS
 - filtering 3-8
 - TTL 5-8
 - tunnel 7-41
 - undeliverable ARP 5-3
 - VLAN 13-3, 13-20
- IP access policy 5-22, B-7
- IP ACL 3-1
 - configuring extended 3-6
 - configuring standard 3-5
 - disabling or enabling 3-3
 - displaying 3-15
 - modifying 3-13
 - named 3-12
 - Syslog 3-2
 - displaying 3-15
- IP address
 - assigning 5-4
 - BootP/DHCP stamp 5-36
 - CIDR notation 5-4
 - virtual 14-1
 - virtual router 9-4
- IP multicast 7-1
 - delivery tree 7-30
 - DVMRP 7-30
 - global parameters 7-2
 - PIM-DM 7-4
 - router
 - displaying configuration 7-45
 - tracing a route 7-44
 - tunnel 7-41
- IP prefix list 8-50
- IP sub-net VLAN 13-1
 - configuring 13-41
- IP TOS
 - QoS 2-2

IP/RIP

- administrative distance 5-40
- advertisement 5-2
 - VRRP suppression 9-5, 9-13
- configuring 5-1
- default network route 5-18
- default route
 - advertising and learning 5-41
- displaying information 5-43
 - ARP cache 5-49
 - interface 5-46
 - IP forwarding cache 5-53
 - IP host cache 5-50
 - RIP filter 5-62
 - route 5-53
 - summary 5-43
 - traffic statistics 5-56
- enabling 5-37
- filter
 - displaying 5-62
- hold down 5-2
- hop count limit 5-2
- interface parameters 5-34
- neighbor filter 5-31, B-17
- parameters 5-6, 5-37, 5-38
- poison reverse update 5-2
- redistribution 5-32, B-26
 - enabling 5-39
 - metric 5-39
- route
 - clearing 5-64
- route filter 5-29, B-16
- split horizon 5-2
- update time 5-38

IPX

- age timer
 - learned routes 11-15
 - learned SAP entries 11-15
- configuring 11-1
 - interface 11-3
- displaying information 11-16
 - forwarding cache 11-19
 - route 11-20
 - server table 11-21
 - summary 11-16
- enabling 11-2
- filter
 - forward 11-5, B-19
 - GNS replies 11-10
- frame type 11-1
- GNS replies
 - disabling 11-11
 - round robin 11-10
- interface
 - configuring 11-3
 - displaying information 11-17
- parameters 11-2
- traffic statistics 11-22
- VLAN 13-3, 13-20

IPX network VLAN 13-1

- configuring 13-42

IPX/RIP

- advertisement interval 11-14
- advertisement packet size 11-13
- filter 11-7, B-19
- hop count increment 11-12
- maximum 11-11

IPX/SAP

- advertisement interval 11-14
- advertisement packet size 11-13
- displaying server table 11-21
- filter 11-9, B-20
- hop count increment 11-12
- maximum 11-11

IRDP 5-9

ISR

- VLAN 13-3, 13-12

J

- Join message interval
 - PIM-SM 7-18

K

Keepalive

- BGP4 8-5, 8-20
- HTTP 14-6
- SRP 10-11
- VRRP 9-14

L

Layer 2

- MAC address filter B-12
- VLAN 13-1, 13-2
 - configuring 13-13, 13-38
 - default 13-5, 13-13
 - modifying 13-17

Layer 3

- VLAN 13-1, 13-3, 13-20, B-6
 - configuring 13-39, 13-41, 13-42, 13-43

Layer 4

- route health injection 14-1

Leaf node

- IP multicast 7-2

Learning

- IP/RIP default route 5-41

Load balancing

- static IP routes 5-16

Load sharing

- BGP4 8-24
- IP 5-10
- OSPF 6-28

Local AS

- BGP4 8-12

Local preference 8-3

Lock

- MAC address B-14

Loopback interface 8-13

LSA

- displaying 6-46
- External
 - displaying 6-44

LSDB

- exit overflow interval 6-35
- maximum 6-34

M

MAC

- address filter B-12
- address lock B-14
- QoS priority 2-16
- virtual router 9-3

Manual nomenclature 1-1

Master

- VRRP 9-13
 - abdication 9-16
 - negotiation 9-4

Match conditions 8-57

Maximum response time

- IGMP 7-3

Membership time

- IGMP 7-3

Memory

- BGP4 8-10
- OSPF
 - LSDB 6-34
 - routes 6-34

Message

- advertisement
 - VRRP 9-4
- BGP4 8-4
- graft
 - DVMRP 7-36
- hello
 - PIM-DM 7-9
 - VRRP 9-14
- hold
 - BGP4 8-20
- join
 - PIM-SM 7-18
- keepalive
 - BGP4 8-20
 - SRP 10-11
 - VRRP 9-14
- probe
 - DVMRP 7-37
- prune
 - DVMRP 7-36
 - PIM-DM 7-9
 - PIM-SM 7-18

Metric

- BGP4 8-27, 8-29
- DVMRP 7-39
- IP 5-36
- OSPF
 - redistribution 6-25, 6-33
- redistribution

- IP/RIP 5-39

Modifying

- OSPF compliance setting 6-38
- OSPF default port parameters 6-38

mrinfo 7-45

mroute 7-42

mtrace 7-44

MTU

- IP 5-35

Multicast

- cache
 - PIM-SM 7-27
- delivery tree 7-30
- filter B-14
- tree
 - IP multicast 7-2

Multi-Exit Discriminator 8-27, 8-29

N

Named IP ACL 3-12

NBP 12-3

Negotiation

- VRRP master 9-4

Neighbor

- BGP4 8-14
 - displaying information 8-79
 - distribute list 8-53
 - maximum 8-21
 - resetting session 8-95
- DVMRP
 - timeout 7-34
- OSPF 6-18
 - displaying information 6-41
- PIM-DM
 - timeout 7-8
- PIM-SM
 - displaying information 7-26
- RIP
 - filter 5-31, B-17

NetBIOS

- enabling 11-3
- VLAN 13-3, 13-20

Network

- AppleTalk 12-1
- default route 5-18
- filter 12-3, 12-13, B-20

Network advertising

- BGP4 8-25

Network mask 5-4, 5-14

Node

- AppleTalk 12-1
- IP multicast 7-1

Non-seed router

- AppleTalk 12-3, 12-7

Not So Stubby Area

- configuring 6-9

NOTIFICATION message 8-5

NSSA

- configuring 6-9

Null route 5-17

O

OPEN message 8-4

Origin

BGP4 8-3

OSPF

administrative distance 6-36

area 6-2

assigning to interface 6-14

configuring 6-7

range 6-2

area range

configuring 6-13

ASBR 6-2

autonomous system 6-1

configuration rules 6-5

configuring 6-1

default route origination 6-32

displaying information 6-38

ABR and ASBR 6-48

area 6-40

External LSA 6-44

interface 6-42

LSA 6-46

neighbor 6-41

route 6-43

summary 6-38

trap status 6-48

virtual link 6-47

virtual neighbor 6-47

DR 6-3

election 6-3

enabling 6-7

exit overflow interval 6-35

interface

blocking LSAs 6-18

defaults 6-16

interface parameters 6-17

load sharing 6-28

LSDB

maximum 6-34

modifying port parameters 6-38

neighbor 6-18

Not So Stubby Area

configuring 6-9

NSSA

configuring 6-9

overview 6-1

parameters 6-6

redistribution 6-22, B-27

enabling 6-26

metric 6-25

metric type 6-33

RFC compliance 6-4, 6-38

route

maximum 6-34

summarization 6-31

SPF

delay 6-33

hold time 6-33

totally stubby area

configuring 6-9

transit area 6-18

trap 6-36

virtual link 6-18

displaying information 6-47

parameters 6-21

virtual neighbor

displaying information 6-47

Other

VLAN 13-3, 13-20

P

Parameters

AppleTalk 12-16

BGP4 8-6

DVMRP

interface 7-38

IP multicast 7-2

IP/RIP 5-6, 5-34, 5-37, 5-38

IPX 11-2

OSPF 6-6

interface 6-17

virtual link 6-21

PIM-DM 7-8, 7-34

interface 7-11

PIM-SM 7-14

interface 7-15

SRP 10-11

VRRP 9-12

Path

PIM-SM 7-13

Path maximum

IP load sharing 5-11

PIM Sparse 7-12

PIM-DM 7-4

configuring 7-7

graft retransmit timer 7-10

hello timer 7-9

inactivity timer 7-11

interface parameters 7-11

neighbor timeout 7-8

prune timer 7-9

PIM-SM 7-12

configuring 7-14

displaying BSR information 7-21

displaying flow cache 7-27

displaying groups 7-20

displaying information 7-18

displaying Multicast cache 7-27

displaying neighbor information 7-26

displaying RP and group information 7-24

displaying RP information 7-23

displaying RP set list 7-25

displaying summary information 7-19

- enabling 7-15
- interface parameters 7-15
- router types 7-13
- statistics 7-18
- traffic statistics 7-29
- PMBR 7-13
- Poison reverse update 5-2
- Policy B-1
 - default action B-3
 - IP access 5-22, B-7
 - precedence B-4
 - QoS B-5
 - scope B-2
 - TCP/UDP access B-9
- Port
 - Layer 2 VLAN 13-1, 13-2
 - logical 13-3, 13-12
 - MAC address lock B-14
 - QoS
 - priority 2-11
 - utilization 2-26
 - statistics A-4
 - STP parameters
 - VLAN 13-20
 - tagged 2-14, 13-5
 - TCP 5-23
 - track
 - SRP 10-3, 10-10, 10-14
 - VRRP 9-5, 9-15
 - track priority
 - VRRP 9-15
 - trunk group
 - VLAN 13-11, 13-13
 - UDP 5-23
 - virtual interface
 - VLAN 13-8
 - VLAN
 - aging 13-32
 - displaying information 13-46
 - dynamic 13-9, 13-32
 - excluded 13-10
 - static 13-10
 - types 13-9
- Port-based VLAN
 - configuring 13-38
 - default 13-5, 13-13
- Preempt
 - VRRP backup 9-15
- Prefix 5-14
- Priority
 - 802.1p 2-14, 13-5
 - AppleTalk socket 2-25
 - port 2-11
 - QoS 2-1
 - assigning 2-11
 - session 2-17
 - static MAC entry 2-16
 - track port
 - SRP 10-3

- VRRP 9-5
- VLAN 2-12, 13-18
- VRRP
 - backup 9-13
- Probe interval timer
 - DVMRP 7-37
- Protocol-based VLAN
 - configuring 13-39
- Proxy ARP 5-11
- Prune
 - DVMRP 7-30, 7-31
 - message interval
 - PIM-SM 7-18
 - PIM-DM 7-4
 - timer
 - DVMRP 7-36
 - PIM-DM 7-9

Q

- QoS
 - configuring 2-1
 - IP TOS 2-2
 - methods 2-3
 - priority
 - 802.1p 2-14, 13-5
 - AppleTalk socket 2-25
 - assigning 2-11
 - port 2-11
 - queues 2-1
 - session 2-17
 - static MAC entry 2-16
 - VLAN 2-12, 13-18
 - queue
 - bandwidth 2-5
 - configuring 2-4
 - displaying configuration 2-10
 - naming 2-4
 - utilization 2-26
- Query
 - AppleTalk ZIP update 12-19
- IGMP
 - disabling 7-3
 - interval 7-2
- Queue
 - QoS
 - bandwidth 2-5
 - configuring 2-4
 - displaying configuration 2-10
 - naming 2-4

R

- RARP 5-12
 - static entry 5-20
- Redistribution B-25
 - BGP4 8-37, B-27
 - IP/RIP 5-32, B-26
 - enabling 5-39
 - metric 5-39
 - metric

- OSPF 6-25
 - OSPF 6-22, B-27
 - enabling 6-26
 - metric type 6-33
 - Redundant Management
 - maximum number of IP routes 6-1, 8-1
 - Regular expressions 8-44
 - Report interval timer
 - DVMRP 7-37
 - Reverse path forwarding 7-30
 - RFC 2178 6-4
 - enabling 6-38
 - RIP. See IP/RIP.
 - RMON A-1
 - Root node
 - IP multicast 7-1
 - Route
 - BGP4
 - aggregation 8-35
 - attributes 8-90
 - flap dampening 8-64
 - maximum 8-22
 - default gateway
 - DVMRP 7-38
 - default network 5-18
 - DVMRP
 - advertisement 7-39
 - IP
 - filter 5-29, B-16
 - static 5-14
 - IP/RIP
 - default 5-41
 - IPX
 - age timer 11-15
 - null 5-17
 - OSPF
 - maximum 6-34
 - redistribution B-25
 - BGP4 8-37, B-27
 - RIP
 - advertisement 5-2
 - source routing 5-13
 - static
 - IP multicast 7-42
 - static IP
 - load balancing 5-16
 - VLAN 13-3, 13-12, 13-21
 - AppleTalk 12-13
 - Route dampening
 - statistics 8-74, 8-92
 - Route discard time
 - DVMRP 7-35
 - Route expire timeout
 - DVMRP 7-35
 - Route flap dampening 8-64
 - statistics
 - clearing 8-73, 8-75, 8-94
 - un-suppressing a route 8-95
 - Route health injection 14-1
 - Route map 8-55
 - match 8-57
 - set 8-61
 - Route reflection 8-31
 - Route summarization
 - BGP4 8-30
 - OSPF 6-31
 - Route synchronization 8-30
 - Route table
 - BGP4 8-2
 - displaying 8-87
 - path selection 8-3
 - IP 5-1
 - displaying 8-92
 - IP/RIP
 - clearing 5-64
 - displaying 5-53
 - IPX
 - displaying 11-20
 - OSPF
 - displaying 6-43
 - Router
 - AppleTalk 12-7
 - Router ID 5-8, 8-12
 - Routing 5-37
 - RP 7-13, 7-16
 - displaying 7-23
 - displaying group information 7-24
 - displaying set list 7-25
 - RTMP 12-3
 - update interval 12-19
- S**
- Security B-1
 - IP access policy 5-22, B-7
 - MAC address lock B-14
 - TCP/UDP access policy B-9
 - VRRP authentication 9-5, 9-12
 - Seed router
 - AppleTalk 12-3, 12-5
 - Server table
 - IPX
 - displaying 11-21
 - Service iii
 - Session
 - QoS priority 2-17
 - Set conditions 8-61
 - Set list 7-25
 - Single STP 4-5
 - Software
 - support
 - AppleTalk 12-3
 - Source routing 5-13
 - SPF
 - delay 6-33
 - hold time 6-33
 - Split horizon 5-2
 - SPT threshold 7-17

SRP

- configuring 10-1, 10-2
- dead interval 10-11
- differences from VRRP 9-6, 10-7
- enabling 10-8
- enabling on the router 10-8
- keepalive time 10-11
- multiple VLANs 13-36
- port parameters 10-11
- routers 10-3
- track port 10-3, 10-10, 10-14
- virtual interface 10-3, 10-14
- virtual router IP address
 - configuring 10-9

Stamp

- BootP/DHCP IP address 5-36

Standard IP ACL 3-5

Standby router

- SRP 10-3

Static IP route 5-14

- load balancing 5-16

Static port 13-10

Static route

- IP multicast
 - configuring 7-42

Statistics

- AppleTalk 12-20
 - clearing 12-21
- BGP4
 - clearing 8-96
- clearing A-5
- IP/RIP 5-56
- IPX 11-22
- PIM-SM 7-18, 7-29
- port A-4
- RMON Group 1 A-1
- route dampening 8-74, 8-92
- STP A-5
- VRRP 9-17
 - clearing 9-18

STP 4-1

- bridge parameters
 - VLAN 13-19
- Fast Port Span 4-1
- Fast Uplink Span 4-3
- single 4-5
- statistics A-5
- VLAN 13-7, 13-19

Strict

- QoS method 2-3

System

- displaying information A-3

T

- Table map 8-63

- Tagged port 2-14, 13-5

- TCP port 5-23

- TCP/UDP access policy B-9

Threshold

- TTL
 - IP 5-8

Time

- update
 - IP/RIP 5-38

Totally stubby area

- OSPF
 - configuring 6-9

Traceroute

- IP multicast 7-44

Track port

- SRP 10-10, 10-14
- VRRP 9-15

Track priority

- VRRP 9-15

Traffic

- QoS
 - bandwidth percentages 2-28
- statistics
 - AppleTalk 12-20
 - BGP4 8-79
 - IP/RIP 5-56
 - IPX 11-22
 - PIM-SM 7-29
 - VRRP 9-17

Transit area

- OSPF 6-18

Trap

- OSPF 6-36
 - displaying status 6-48

Trigger interval timer

- DVMRP 7-37

Trunk group

- VLAN 13-11, 13-13

TTL

- DVMRP 7-38
- IP 5-8

U

- UDP helper 5-41

- UDP port 5-23

- Undeliverable IP ARP 5-3

- UPDATE message 8-4

Update time

- IP/RIP 5-38

Upstream router

- IP multicast 7-1

Utilization

- QoS 2-26

V

- VIP 14-1

- Virtual Interface 13-7

- Virtual interface 13-3, 13-12, 13-21

- SRP 10-3, 10-14

- VLAN 13-8

- AppleTalk 12-13

- Virtual link
 - OSPF 6-18
 - displaying information 6-47
 - parameters 6-21
- Virtual neighbor
 - OSPF
 - displaying information 6-47
- Virtual router 9-3
 - configuring 9-8
- VLAN
 - AppleTalk
 - routing 12-13
 - AppleTalk Cable 13-4
 - AppleTalk cable 13-1, 13-29
 - AppleTalk protocol 13-4
 - ARP 13-36
 - broadcast leaks 13-10
 - configuring 13-1
 - default 13-5, 13-13
 - displaying information 13-45
 - displaying port information 13-46
 - displaying summary information 13-45
 - dynamic port 13-9, 13-32
 - aging 13-32
 - excluded port 13-10
 - IP sub-net 13-1
 - IP subnet 13-4
 - IPX network 13-1, 13-4
 - ISR 13-3, 13-12
 - Layer 2 port-based 13-1, 13-2
 - Layer 3 protocol-based 13-1, 13-3, 13-20, B-6
 - multiple, same IP subnet address 13-36
 - port-based 13-11, 13-13, 13-17
 - protocol, limit 13-11
 - QoS priority 2-12, 13-18
 - route 13-12
 - static port 13-10
 - STP 13-7, 13-19
 - subnet or network limit 13-11
 - trunk group 13-11, 13-13
 - types 13-1
 - virtual interface 13-3, 13-7, 13-8, 13-12, 13-21
- VLAN 4094 13-8
- VRID 9-3, 9-8
 - IP address 9-4
 - MAC address 9-3
- VRRP
 - abdication 9-16
 - advertisement 9-4
 - authentication 9-5, 9-12
 - backup 9-13
 - priority 9-13
 - backup preempt 9-15
 - configuring 9-1, 9-2
 - dead interval 9-14
 - differences from SRP 9-6, 10-7
 - displaying information 9-17
 - displaying summary information 9-17
 - enabling 9-6, 9-7
 - hello timer 9-14
 - keepalive time 9-14
 - master 9-13
 - master negotiation 9-4
 - multiple VLANs 13-36
 - parameters 9-12
 - RIP advertisement suppression 9-5, 9-13
 - statistics 9-17
 - clearing 9-18
 - track port 9-5, 9-15
 - track priority 9-15
 - virtual router IP address 9-4
 - virtual router MAC address 9-3
 - VRID 9-3
 - configuring 9-8

W

- Warranty ii
- Weight
 - BGP4 8-3
- Weighted
 - QoS method 2-3

Z

- ZIP query interval 12-19
- Zone
 - AppleTalk 12-2, 12-5
 - filter 12-2, 12-10, B-20