
Index

Numerics

- 802.1p priority (QoS)
 - definition ... 6-6
- 802.1Q VLAN standard ... 5-7
- 802.1w as a region ... 5-54

A

- active path ... 5-5
- address
 - IP ... 7-8
- advertisement ... 3-3
- applicable products ... 1-ii
- ARP
 - age setting ... 7-10
 - cache ... 7-4
 - cache table ... 7-4
 - configuring parameters ... 7-8
 - how it works ... 7-8
 - proxy ... 7-11
- assigning
 - IP address ... 7-8
- auto port setting ... 4-5

B

- bandwidth
 - effect of QoS ... 6-1
- bandwidth loss, spanning tree ... 5-51
- blocked link from STP operation ... 5-9, 5-52
- blocked port
 - from IGMP operation ... 4-5
 - from STP operation ... 5-8, 5-50
- Bootp
 - gateway ignored ... 2-7
- BPDU ... 3-3, 5-7
- bridge protocol data unit
 - See* BPDU.
- broadcast domain ... 2-3
- broadcast storm ... 5-5, 5-11
- broadcast traffic
 - enabling forwarding of directed ... 7-12

C

- caches
 - ARP ... 7-4
 - IP forwarding ... 7-5
- CIDR ... 7-8
- CLI
 - configuring RSTP ... 5-14
- configuration ... 5-8, 5-50, 7-17
 - ARP parameters ... 7-8
 - Class of Service ... 6-14
 - default route ... 7-17
 - DHCP Relay ... 7-24
 - factory default ... 2-14, 2-19, 5-9, 5-49
 - ICMP ... 7-13
 - IP routing forwarding parameters ... 7-11
 - IP routing parameters ... 7-8
 - IRDP ... 7-20
 - RSTP
 - from the CLI ... 5-14
 - from the menu ... 5-20
 - per-port parameters ... 5-18
 - whole switch parameters ... 5-16
 - spanning tree protocol ... 5-8, 5-50
 - static IP routes ... 7-15, 7-16
 - VLAN ... 2-3
- configuring RSTP ... 5-13
- copyright ... 1-ii
- CoS
 - See* Class of Service.

D

- data-driven IGMP ... 4-15
- dedicated management VLAN ... 2-6
- default route ... 7-17
- DHCP
 - gateway ignored ... 2-7
 - Option 82 ... 7-26
- DHCP Relay
 - configuration ... 7-24
 - enabling ... 7-25
 - helper address ... 7-25
 - minimum requirements ... 7-25

- DHCP-Relay
 - operation with Option 82 ... 7-29
- directed broadcasts ... 7-12
- disclaimer ... 1-i
- displaying information
 - IRDP ... 7-23
- domain ... 2-14, 2-19
- downstream device (QoS)
 - definition ... 6-6
 - effect of priority settings ... 6-10
- DSCP
 - Policy Table ... 6-65
 - policy, defined ... 6-6
 - See also* priority.

E

- enabling RSTP
 - CLI ... 5-15
 - menu interface ... 5-20
 - web browser interface ... 5-22
- enabling STP
 - CLI ... 5-15
- Exclude Source
 - See* IGMP.

F

- fast mode
 - spanning tree ... 5-24, 5-30
- filters
 - effect of IGMP ... 4-23
 - maximum allowed ... 4-23
- forbid
 - See* GVRP.
- forwarding
 - directed broadcasts ... 7-12
- forwarding database
 - See* VLAN.
- forwarding parameters, IP routing
 - configuring ... 7-11
- forwarding port, IGMP ... 4-5

G

- GARP
 - See* GVRP. ... 3-3
- gateway, manual config ... 2-7

- GVRP ... 5-48
 - advertisement ... 3-17
 - advertisement, defined ... 3-3
 - advertisement, responses to ... 3-5
 - advertisements, generating ... 3-10
 - auto option ... 3-9
 - benefit ... 3-3
 - block ... 3-7
 - CLI, configuring ... 3-13
 - configurable port options ... 3-6
 - configuring learn, block, disable ... 3-7
 - convert dynamic to static ... 3-6
 - converting to static VLAN ... 3-3
 - disable ... 3-7
 - dynamic VLAN and reboots ... 3-17
 - dynamic VLANs always tagged ... 3-4
 - Effect on maximum allowed VLANs ... 2-22
 - forbid option ... 3-9
 - GARP ... 3-3
 - general operation ... 3-4
 - IP addressing ... 3-6
 - learn ... 3-7
 - learn, block, disable ... 3-9
 - menu, configuring ... 3-12
 - non-GVRP aware ... 3-17
 - non-GVRP device ... 3-17
 - operating notes ... 3-17
 - port control options ... 3-10
 - port-leave from dynamic ... 3-10
 - reboot, switch ... 3-10
 - recommended tagging ... 3-10
 - standard ... 3-3
 - tagged, dynamic VLAN ... 3-4
 - unknown VLAN ... 3-10
 - unknown VLAN, options ... 3-6
 - VLAN behavior ... 2-8
 - VLAN, dynamic adds ... 2-17
 - VLAN, maximum ... 3-17
 - with QoS ... 6-52

H

- helper address for DHCP Relay ... 7-25

I

- ICMP
 - configuring ... 7-13

IGMP

- benefits ... 4-3
 - configuration ... 4-11
 - configure per VLAN ... 4-5
 - data-driven ... 4-15
 - delayed group flush ... 4-17
 - effect on filters ... 4-23
 - Exclude Source ... 4-13
 - Fast-Leave ... 4-14
 - forced fast-leave ... 4-17
 - high-priority forwarding ... 4-5
 - Include Source ... 4-13
 - IP multicast address range ... 4-23
 - leave group ... 4-12
 - maximum address count ... 4-23
 - multicast group ... 4-11
 - multimedia ... 4-3
 - operation ... 4-11, 4-12
 - port states ... 4-5
 - query ... 4-11
 - report ... 4-12
 - status ... 4-12
 - supported standards and RFCs ... 4-13
 - traffic ... 4-5
 - Version 3 ... 4-13
- inbound port (QoS)
- definition ... 6-6
- Include Source
- See* IGMP.
- interface, VLAN
- enabling IRDP ... 7-21
- ## IP
- gateway ... 2-7
 - traffic priority based on ToS field ... 6-39
- ## IP address
- assigning ... 7-8
 - CIDR notation ... 7-8
- IP forwarding cache ... 7-5
- IP global parameters ... 7-6
- IP interface parameters ... 7-7
- IP route table ... 7-5
- ## IP routing
- ARP age ... 7-10
 - ARP cache table ... 7-4
 - changing ARP parameters ... 7-8
 - configuring static routes ... 7-15
 - default route ... 7-17
 - DHCP Relay configuration ... 7-24

- directed broadcasts ... 7-12
- forwarding cache ... 7-5
- forwarding parameters ... 7-11
- global parameters ... 7-6
- ICMP configuration ... 7-13
- interface parameters ... 7-7
- IRDP configuration ... 7-20
- null static route ... 7-17
- overview ... 7-3
- parameter configuring ... 7-8
- Proxy ARP, enabling ... 7-11
- routing table ... 7-5
- static route configuration ... 7-16
- static route types ... 7-15
- tables and caches ... 7-4
- VLAN interface ... 7-3

IP, type of service

- configuring priority ... 6-39

IRDP

- configuring ... 7-20
- displaying information ... 7-23
- enabling globally ... 7-21
- enabling on VLAN interface ... 7-21

L

leave group

See IGMP

legacy VLAN ... 2-5

loop, network ... 5-6, 5-8, 5-50

M

MAC address

- duplicate ... 2-9
- single forwarding database ... 2-9
- VLAN ... 2-35

MAC address, per switch ... 2-9

MAC address, per VLAN ... 2-9

maximum VLANs, GVRP ... 3-17

menu interface

- configuring RSTP ... 5-20

mesh

- spanning tree ... 5-55

message

- VLAN already exists ... 2-25

MSTI, configuration ... 5-65

MSTP

See spanning-tree, 802.1s.
multicast group
 See IGMP.
multimedia
 See IGMP.
multiple ... 2-9
multiple forwarding database ... 2-9

N

notes on using VLANs ... 2-9
notices ... 1-ii
null static route ... 7-17

O

optimizing RSTP configuration ... 5-13
Option 82 (DHCP) ... 7-26
outbound port (QoS)
 definition ... 6-6
outbound port queue (QoS)
 definition ... 6-7
overview, IP routing ... 7-3

P

parameters
 IP global ... 7-6
 IP interface ... 7-7
path cost ... 5-9
Perlman, *Interconnections* ... 5-32
port
 auto, IGMP ... 4-5
 blocked by STP operation ... 5-8, 5-50
 blocked, IGMP ... 4-5
 forwarding, IGMP ... 4-5
 groups, 2600 ... 6-17
 loop ... 5-8, 5-50
 monitoring ... 2-36
 redundant path ... 5-8, 5-50
 state, IGMP control ... 4-5
port groups, 2600 ... 6-17
port trunk
 VLAN ... 2-35
 with fast-uplink STP ... 5-44
precedence bits (QoS)
 definition ... 6-6
primary VLAN

See VLAN.

priority ... 4-5
 802.1p priority, defined ... 6-6
 codepoint, defined ... 6-6
 downstream device, defined ... 6-6
 DSCP policy, defined ... 6-6
 DSCP, defined ... 6-6
 inbound port, defined ... 6-6
 outbound port, defined ... 6-6
 upstream device, defined ... 6-7
priority (QoS)
 criteria for prioritizing packets ... 6-10
 type of service screen ... 6-39
 VID, effect of eliminating ... 6-52
 VLAN ID priority ... 6-52, 6-58
priority QoS)
 device priority screen ... 6-33
 IP address, source and destination match ... 6-34
Proxy ARP, enabling ... 7-11
publication data ... 1-ii

Q

Quality of Service
 basic operation ... 6-8
 configuring ... 6-14, 6-25
 configuring IP type of service ... 6-39
 criteria for prioritizing outbound packets ... 6-10
 definitions of terms ... 6-6
 device priority screen ... 6-33
 DSCP Policy Table ... 6-65
 GVRP not supported ... 6-52
 maximum entry limit ... 6-73
 no override definition ... 6-26
 No override, effect of ... 6-66
 overview ... 6-1
 port groups, 2600 ... 6-17
 prioritizing ... 6-16
 prioritizing traffic based on IP ToS field ... 6-39
 priority settings map to outbound queues ... 6-9
 priority settings mapped to downstream
 devices ... 6-10
 QoS passthrough-mode ... 6-5
 qos resources help ... 6-18
 resource planning ... 6-16
 resource usage ... 6-16
 resources exceeded ... 6-19
 rule maximums per-port ... 6-16

- rule resource usage, 2600 ... 6-17
- rule resource usage, 2800 ... 6-17
- rules available per-port ... 6-18
- rules, insufficient ... 6-18
- show qos resources ... 6-18
- type of service screen ... 6-39
- VLAN ID priority ... 6-52, 6-58

query

See IGMP.

quick start ... 1-6

R

reboot ... 3-10

redundant path ... 5-8, 5-50

spanning tree ... 5-9

region ... 5-49

See spanning-tree, 802.1s.

report

See IGMP

revision number ... 5-53

router ... 4-11

routing

configuring static routes ... 7-15

default route ... 7-17

DHCP Relay configuration ... 7-24

IP static routes ... 7-16

IRDP configuration ... 7-20

null static route ... 7-17

static route types ... 7-15

RSTP

configuring ... 5-13

configuring per-port parameters ... 5-18

configuring whole switch parameters ... 5-16

configuring with the CLI ... 5-14

configuring with the menu ... 5-20

edge-port parameter ... 5-18

enabling from CLI ... 5-15

enabling from the menu ... 5-20

enabling with the web browser ... 5-22

mcheck parameter ... 5-18

optimizing the configuration ... 5-13

path-cost parameter ... 5-18

point-to-point-mac parameter ... 5-18

priority parameter ... 5-18

viewing the configuration ... 5-14

S

server

access failure ... 5-8

setup screen ... 1-6

single forwarding database ... 2-9

spanning tree

802.1Q standard ... 5-7

802.1s

See spanning tree, 802.1s.

blocked link ... 5-9, 5-52

blocked port ... 5-8, 5-50

BPDU ... 5-7

broadcast storm ... 5-5, 5-11

caution, fast-uplink ... 5-32

configuring per-port parameters ... 5-18

configuring RSTP ... 5-13

configuring whole-switch parameters ... 5-16

configuring with the menu ... 5-20

description of operation ... 5-8

enabling from the browser interface ... 5-45

enabling in the CLI ... 5-28

enabling MSTP ... 5-72

enabling RSTP ... 5-15

enabling STP ... 5-15

fast mode ... 5-24, 5-30

fast-uplink terminology ... 5-33

fast-uplink, configuring ... 5-43

fast-uplink, menu ... 5-35

fast-uplink, operating notes ... 5-44

fast-uplink, viewing status, CLI ... 5-41

fast-uplink, viewing status, menu ... 5-39

fast-uplink, with port trunks ... 5-44

loop, network ... 5-6

MSTP

See spanning-tree, 802.1s

redundant path ... 5-5

RSTP edge port parameter ... 5-18

RSTP mcheck parameter ... 5-18

RSTP path-cost parameter ... 5-18

RSTP point-to-point-mac parameter ... 5-18

RSTP priority parameter ... 5-18

rules, operating, fast-uplink ... 5-34

viewing the configuration ... 5-14

VLAN effect on ... 2-34

with 802.1Q VLANs ... 5-9

spanning tree protocol

See STP.

spanning-tree, 802.1s ... 5-5, 5-46

- 802.1D and 802.1w connections ... 5-54
- 802.1D as a region ... 5-53, 5-54
- 802.1D connection requirement ... 5-64
- 802.1Q VLANs ... 5-51
- 802.1s standard-compliant ... 5-46
- 802.1w as a region ... 5-53
- activation ... 5-60
- active path ... 5-50
- active paths ... 5-54
- bandwidth loss ... 5-51
- benefit ... 5-46
- blocked traffic ... 5-51
- boundary port, region ... 5-53, 5-54
- boundary port, VLAN membership ... 5-51
- BPDU ... 5-51, 5-57, 5-61, 5-62, 5-64
- BPDU requirement ... 5-53
- BPDU, function ... 5-53
- bridge ... 5-53
- bridge, designated for region ... 5-53
- caution ... 5-46, 5-49
- CIST ... 5-47, 5-52, 5-54
- CIST per-port hello time ... 5-54
- CIST root ... 5-64
- common and internal spanning tree
 - See* CIST.
- common spanning tree
 - See* CST.
- compatibility ... 5-55
- compatibility mode ... 5-62
- configuration ... 5-59, 5-72
- configuration identifier ... 5-53
- configuration steps ... 5-57
- configuration, exchanging ... 5-72
- configuration, MST instance ... 5-65
- configuration, MSTI per-port ... 5-69
- configuration, port ... 5-63
- convergence time, minimize ... 5-60
- CST ... 5-48, 5-51, 5-53
- CST and legacy devices ... 5-51
- CST, view status ... 5-74, 5-75
- default configuration ... 5-49
- designated bridge ... 5-51, 5-53
- designated port ... 5-51
- disabling MSTP ... 5-72
- display statistics and configuration ... 5-74
- dynamic VLANs, disallowed ... 5-48
- edge port ... 5-63
- enabling a region ... 5-72
- enabling MSTP ... 5-72
- example of multiple topologies ... 5-50
- fault tolerance ... 5-46
- force protocol version ... 5-55
- force-version ... 5-64
- forwarding paths ... 5-55
- forwarding state ... 5-63
- frame duplication and misordering ... 5-55
- general operation ... 5-5, 5-46
- GVRP ... 5-48, 5-55
- hello-time, CIST root, propagated ... 5-54, 5-62
- hello-time, override ... 5-54
- hello-time, propagated ... 5-54
- hop-count decremented ... 5-61
- instance ... 5-5, 5-54, 5-58
- instance, forwarding topology ... 5-54
- instance, IST ... 5-48
- instance, type ... 5-48
- internal spanning tree
 - See* IST.
- interoperating with 802.1D and 802.1w ... 5-53
- IST ... 5-48
- IST instance ... 5-48, 5-66
- IST root ... 5-48, 5-50, 5-53
- IST, defined ... 5-53
- IST, dynamic VLAN ... 5-55
- IST, root switch ... 5-53
- IST, switch membership ... 5-53
- IST, VLAN membership ... 5-48
- legacy devices and the CST ... 5-51
- legacy STP and RSTP ... 5-51
- mesh environment ... 5-46, 5-55
- MIB ... 5-81
- MST region
 - See* region.
- MSTI ... 5-48, 5-64
- MSTI root ... 5-50
- MSTI, view status ... 5-76
- MSTP ... 5-49
- MSTP operation ... 5-49
- MSTP, view global configuration ... 5-77
- multiple spanning tree instance
 - See* MSTI
- override hello-time ... 5-54
- path cost, effect on 802.1D ... 5-55
- pending configuration ... 5-80
- pending option ... 5-49, 5-61, 5-72, 5-73
- per-VLAN STP ... 5-46

- planning ... 5-56
- port connectivity ... 5-63
- port states ... 5-50, 5-55
- priority resolution ... 5-67
- priority, device ... 5-58, 5-68
- priority, IST port ... 5-71
- priority, MSTI port ... 5-70
- rapid state transitions ... 5-55, 5-57
- redundant links ... 5-51
- region ... 5-5, 5-47, 5-48
- region name ... 5-53, 5-60
- region root switch ... 5-48
- region, configuration name ... 5-81
- region, Configuration Revision number ... 5-81
- region, defined ... 5-53
- region, enabling ... 5-72
- region, root bridge ... 5-52
- region, RSTP bridge ... 5-54
- region, switch configuration ... 5-54
- region, switch excluded ... 5-81
- region, view configuration ... 5-79
- region, VLAN assignments ... 5-53
- regional boundary port ... 5-53
- regional root bridge per-instance ... 5-51
- regional root switch ... 5-53
- regional root switch, configuration ... 5-54
- regions, communication between ... 5-54
- root bridge ... 5-47
- root bridge per-instance ... 5-51
- root bridge per-region ... 5-52
- root port per-instance ... 5-51
- root switch, instance ... 5-67
- root switch, IST instance ... 5-48, 5-53
- root switch, MST instance ... 5-54
- root switch, regional ... 5-53, 5-54
- root, CIST ... 5-62
- root, IST ... 5-53
- root, MSTI ... 5-50
- routed traffic in a region ... 5-51
- RSTP as a region ... 5-47
- RSTP BPDU requirement ... 5-53
- RSTP bridge ... 5-54
- rules for operation ... 5-54
- separate forwarding paths ... 5-48
- show commands ... 5-74
- SNMP MIB ... 5-81
- STP as a region ... 5-47
- switch excluded from region ... 5-81
- topology between regions ... 5-49
- trunk, root, per-instance ... 5-51
- trunked link ... 5-77
- trunked link example ... 5-52
- types of MST instances ... 5-48
- VLAN assignments, region ... 5-53, 5-54
- VLAN membership, region ... 5-52
- VLAN, change instance ... 5-58
- VLAN, configuration error ... 5-81
- VLAN, connectivity between regions ... 5-54
- VLAN, duplicate or missing packets ... 5-81
- VLAN, dynamic ... 5-48
- VLAN, instance assigned ... 5-50, 5-54, 5-66
- with legacy STP and RSTP ... 5-47
- stacking
 - benefits ... 8-4, 8-5
 - minimum software version, other ProCurve switches ... 8-10
 - primary ... 8-46
 - See also* virtual stacking.
- static IP routes
 - configuring ... 7-15, 7-16
 - IP routing
 - static route parameters ... 7-16
 - maximum ... 7-15
 - route types ... 7-15
- static VLAN, convert to ... 3-3
- STP
 - enabling from the CLI ... 5-15
 - server access failure ... 5-8
- subnet ... 4-12
- subnet address ... 2-4

T

- tables
 - ARP cache ... 7-4
 - IP ... 7-4
 - IP route ... 7-5
- tagged VLAN
 - See* VLAN.
- ToS
 - See* Class of Service.
- trunk, spanning-tree example ... 5-52
- Type of Service
 - using to prioritize IP traffic ... 6-39
- Type of Service field (IP)
 - configuring packet priority ... 6-39

how the switch uses it ... 6-51

U

upstream device (QoS)
definition ... 6-7

V

VID

See VLAN.

Viewing

spanning tree configuration ... 5-14

virtual stacking

transmission interval range ... 8-17

VLAN ... 2-3, 2-35

802.1Q ... 5-9

convert dynamic to static ... 3-3

dedicated management ... 2-6

DEFAULT_VLAN ... 2-6

deleting ... 2-36

DHCP, primary VLAN ... 2-7

duplicate MAC address ... 2-9

dynamic ... 2-3, 2-9

effect on spanning tree ... 2-34

gateway, IP ... 2-7

IGMP configuration ... 4-5

limit ... 2-14

MAC address ... 2-35

maximum, GVRP ... 3-17

multiple forwarding database ... 2-9, 2-13

multiple VLANs on port ... 2-28

notes on using ... 2-9

number allowed, including dynamic ... 2-17

port assignment ... 2-17

port configuration ... 2-29

port monitoring ... 2-36

port restriction ... 2-36

port trunk ... 2-35

primary ... 2-7, 8-10, 8-34, 8-46

primary VLAN ... 2-6

primary, CLI command ... 2-20, 2-22

primary, select in menu ... 2-15

primary, web configure ... 2-25

primary, with DHCP ... 2-9

prioritizing traffic from with QoS ... 6-52, 6-58

restrictions ... 2-36

See also GVRP.

single forwarding database ... 2-9

spanning tree operation ... 5-9

stacking, primary VLAN ... 2-7

static ... 2-3, 2-7, 2-14, 2-19

switch capacity ... 2-4

tagged ... 2-4

tagging ... 2-26, 2-28

unknown VLAN ... 3-10

untagged ... 2-5, 2-18

VID ... 2-3, 2-27

VID, default VLAN ... 2-7

VLAN already exists, message ... 2-25

VLAN interface

description ... 7-3

enabling IRDP ... 7-21

IP routing parameters ... 7-7

VLAN, dynamic ... 5-55

VLANs

maximum ... 2-3, 2-22

maximum, effect of GVRP ... 2-22

static, 802.1s spanning tree ... 5-48

W

warranty ... 1-ii

web browser interface

enabling RSTP ... 5-22

web browser interface, for configuring

IGMP ... 4-11

STP ... 5-45

write memory ... 3-17