

Master Index

B = Basic Management and Configuration Guide
A = Advanced Management and Configuration Guide

Numerics

2B1Q line coding, for BRI ISDN ... B:8-9, A:3-7, A:3-9
802 Slow Protocol frame ... A:14-3
802.1Q
 encapsulation ... B:3-19
 support for ... B:3-16
 tag ... B:3-16
802.1X protocol ... B:2-65

A

AAA subsystem
 accounting ... B:2-27
 access to basic or enable mode ... B:2-28
 assigning named list ... B:2-30
 new connections ... B:2-29
 outbound Telnet connections ... B:2-29
 advantages of ... B:2-15
 authentication
 assigning named list ... B:2-21
 banner ... B:2-22
 configuring ... B:2-17
 failure message ... B:2-22
 named list for enable mode ... B:2-18
 named list for management access ... B:2-19
 prompts ... B:2-22
 authorization ... B:2-24
 access to basic or enable mode ... B:2-24
 assigning named list ... B:2-26
 enabling for console line ... B:2-27
 immediate access to enable mode ... B:2-25
 configuring through CLI ... B:2-15
 configuring through Web browser
 interface ... B:14-35
 criteria for failure ... B:2-16
 debug command for ... B:2-39
 enabling ... B:2-17
 RADIUS server ... B:2-31
 TACACS server ... B:2-35
 troubleshooting ... B:2-39
 using with Xauth ... A:10-50, A:10-51
AAL ... B:7-20

AAL5SNAP ... B:7-20
ABM ... B:6-40
access control
 AAA subsystem ... B:2-15
 ACLs and ACPs ... A:5-4
 management access to router ... B:2-4
access policy sessions
 clearing ... A:5-56
 viewing ... A:5-53
accounting
 with AAA subsystem ... B:2-27
ACL
 action taken ... A:5-35
 applying to interface ... A:5-6, A:5-19
 clear counters ... A:5-58
 command syntax ... A:5-9
 configuring through Web browser
 interface ... A:16-41
 creating ... A:5-9
 debug ... A:5-59
 defined ... A:5-4
 deleting ... A:5-18
 descriptive tag ... A:5-17
 different from ACP ... A:5-5
 editing ... A:5-18
 entry order ... A:5-16
 examples ... A:5-23
 extended
 command syntax for entry ... A:5-12
 defined ... A:5-7
 destination address ... A:5-12
 destination port ... A:5-14
 for demand routing ... B:8-19, A:3-18
 implicit deny any ... B:8-21
 log option ... B:8-21, A:5-15
 packet bits ... A:5-15
 permit entry ... A:5-12
 source address ... A:5-12
 source port ... A:5-14
 specify protocol ... A:5-12
 for FTP access ... A:5-21
 for HTTP access ... A:5-22
 for NAT ... A:6-8
 many-to-one ... A:6-9
 one-to-one ... A:6-11, A:6-13

- for VPN traffic
 - applying to crypto map ... A:10-38, A:10-45
 - configuring ... A:10-35
 - matching an outgoing packet ... A:10-22
 - restricting traffic ... A:10-36
 - troubleshooting ... A:10-75
 - processing entries in ... A:5-16
 - QoS ... A:8-13
 - CBWFQ ... A:8-23
 - LLQ ... A:8-39
 - packet marking ... A:8-47
 - standard
 - command syntax for entry ... A:5-9
 - defined ... A:5-7
 - deny entry ... A:5-12
 - entry ... A:5-9
 - implicit deny any ... A:5-11
 - log ... A:5-11
 - specifying source address ... A:5-9
 - troubleshooting ... A:5-56
 - viewing ... A:5-51
- ACP
- ACL
 - as traffic selector ... A:5-36
 - configure ... A:5-27
 - extended ... A:5-32
 - standard ... A:5-29
 - assign to interface ... A:5-38, A:6-16
 - command syntax for ... A:5-36
 - configuring through Web browser interface ... A:16-44
 - configuring, for NAT ... A:6-13
 - creating ... A:5-36
 - defined ... A:5-4
 - different from ACL ... A:5-5
 - editing ... A:5-37
 - entry
 - command syntax for ... A:5-37
 - importance of order ... A:5-39
 - examples of ... A:5-47
 - flow chart ... A:5-43
 - for Telnet access ... A:5-23
 - implicit “discard all” ... A:5-36
 - logging matches ... A:4-27
 - monitoring connections ... A:6-21
 - processing ... A:5-39
 - summary of action taken ... A:5-42
 - traffic flow through interface ... A:5-44
 - viewing ... A:5-51
 - active sessions ... A:5-53
 - for NAT ... A:6-17
 - statistics ... A:5-54, A:6-19
- administrative distance
- default, for OSPF ... B:15-39
 - default, for static and dynamic routes ... B:11-11, B:15-11
 - in floating static route ... B:11-17
 - selecting routes based on ... B:11-8
 - setting, for BGP routes ... B:15-108
 - specifying ... B:11-16
 - specifying for DHCP client ... B:13-27
- ADSL
- ADSL Lite ... B:7-10
 - ADSL2 ... B:7-5
 - ADSL2+ ... B:7-5
 - Annex A ... B:7-8, B:7-9
 - Annex B ... B:7-8, B:7-9
 - distance supported ... B:7-5
 - downstream traffic ... B:7-4
 - DSLAM ... B:7-7
 - elements of, connection ... B:7-6
 - infrastructure ... B:7-7
 - READSL2 ... B:7-6
 - See also* ADSL interface
 - showtime ... B:7-13
 - splitterless ... B:7-10
 - splitters ... B:7-9
 - upstream traffic ... B:7-4
- ADSL interface
- accessing ... B:7-12
 - activating ... B:7-13
 - binding to ATM interface ... B:7-28
 - configuring through CLI ... B:7-12
 - configuring through Web browser interface ... B:14-78
 - Data Link Layer for ... B:7-7, B:7-17
 - debug commands ... B:7-48
 - force retraining ... B:7-16
 - port number ... B:7-12
 - See also* ADSL
 - slot number ... B:7-12
 - SNR-Margin ... B:7-15
 - SNR-margin monitors ... B:7-16
 - training mode ... B:7-13, B:7-15
 - troubleshooting ... B:7-47
 - viewing status of ... B:7-42

- ADSL module
 - ADSL2+ Annex A ... B:7-11
 - ADSL2+ Annex B ... B:7-11
 - supported standards ... B:7-11
- AF ... A:8-22
 - DiffServ values ... A:8-22
 - DSCP ... A:8-22
- AF traffic classes ... A:8-8, A:8-9
 - DiffServ values ... A:8-9
 - subclasses ... A:8-9, A:8-22
- AH
 - authenticating a packet ... A:10-6
 - finding algorithm used by peer ... A:10-84
 - header ... A:10-5
 - incompatibility with NAT-T ... A:10-32
 - manually defining key for ... A:10-67, A:10-68
 - specifying algorithm for ... A:10-41, A:10-65
- ALG
 - configuring ... A:4-18
 - definition of ... A:4-7
 - FTP ... A:4-19
 - H.323 ... A:4-19
 - PPTP ... A:4-20
 - SIP ... A:4-19
 - supported by ProCurve Secure Router ... A:4-8
- algorithm ... A:10-6
 - See also* encryption algorithm and hash algorithm
- allows ... B:2-25
- analog backup ... A:3-5
 - See also* modem interface and backup
- application-level gateway
 - See* ALG
- area border router
 - See* OSPF, ABR
- ARM ... B:6-40
- AS
 - definition of ... B:15-7
 - routing between ... B:15-7, B:15-67
 - with OSPF ... B:15-38
- ASBR
 - See* OSPF, ASBR
- assured forwarding
 - See* AF
- asymmetric DSL
 - See* ADSL
- Asynchronous Balanced Mode ... B:6-40
- Asynchronous Response Mode ... B:6-40
- ATM adaptation layer ... B:7-20
- ATM interface
 - activating ... B:7-17
 - binding to ADSL interface ... B:7-28
 - configuring through Web browser
 - interface ... B:14-80
 - creating ... B:7-17
 - subinterface
 - AAL configuration ... B:7-20
 - activating ... B:7-19
 - as a DHCP client ... B:7-21
 - as an unnumbered interface ... B:7-25
 - binding to PPP for PPPoA ... B:7-39
 - binding to PPP for PPPoE ... B:7-34
 - configuring ... B:7-18
 - creating ... B:7-18
 - debug commands ... B:7-50
 - IP address ... B:7-20
 - network monitoring ... B:7-24
 - OAM ... B:7-27
 - PVC ... B:7-18, B:7-19
 - RBE ... B:7-41
 - troubleshooting ... B:7-50
 - viewing status of ... B:7-45
 - VPI/VCI ... B:7-19
 - troubleshooting ... B:7-49
 - troubleshooting OAM ... B:7-50
 - viewing status of ... B:7-45
- attack checking ... A:4-6, A:4-9
 - Denial of Service ... A:4-10
 - drop packets ... A:4-9
 - enabling firewall ... A:4-14
 - logging attacks ... A:4-26
 - optional checks ... A:4-15
 - reflexive traffic ... A:4-12, A:4-16
 - SYN-flood attack check ... A:4-16
 - types of attacks ... A:4-9, A:4-14
 - WinNuke attack check ... A:4-15
- authentication
 - failure of AAA methods ... B:2-16
 - RADIUS server ... B:2-31
 - TACACS+ server ... B:2-35
 - with AAA subsystem ... B:2-17
- Authentication Header
 - See* AH
- auto MDIX, Ethernet ports ... B:3-2
- autonomous system
 - See* AS

- AutoSynch™ ... B:1-34
 - configuring with Web browser interface ... B:14-8, A:16-7
 - enabling ... B:1-61, A:1-19
 - troubleshooting ... B:1-71

B

- B channel for ISDN ... B:8-4
- backup
 - choices for configuring ... A:3-11, A:3-14
 - demand routing for ... A:3-12
 - See also* demand routing
 - failover conditions ... A:3-11
 - LEDs ... B:1-25
 - module ... B:1-19
 - persistent backup connections ... A:3-14
 - backup call modes ... A:3-64
 - described ... A:3-14
 - dial list ... A:3-65
 - dial-up process ... A:3-62
 - example of ... A:3-17
 - floating static route for ... A:3-69
 - IP address for PPP interface ... A:3-58
 - monitoring dial-up ... A:3-89
 - multiple ... A:3-71
 - PPP authentication ... A:3-58
 - PPP interface ... A:3-57
 - primary connection settings ... A:3-60
 - troubleshooting ... A:3-86
 - viewing dial list ... A:3-88
- basic mode context ... B:1-36
 - clear commands ... B:1-39
 - commands ... B:1-39
 - show commands ... B:1-41
- BGP ... B:15-67, B:15-106
 - advantages ... B:15-68
 - advertising a network ... B:15-73, B:15-172
 - clear session ... B:15-166
 - compared to RIP and OSPF ... B:15-9
 - configuration examples ... B:15-109
 - configuration tasks ... B:15-71, B:15-72
 - default administrative distance ... B:15-11
 - enabling ... B:15-73
 - exterior gateway protocol ... B:15-7
 - intervals ... B:15-108
 - load balancing ... B:15-76, B:15-77, B:15-78, B:15-86

- local AS ... B:15-75
 - advertising external traffic ... B:15-172
 - viewing ... B:15-169
- messages ... B:15-71
- multihoming ... B:15-70, B:15-85
 - troubleshooting ... B:15-174
- neighbor ... B:15-70
 - configuration ... B:15-75
 - neighbor ID ... B:15-75, B:15-169
 - troubleshooting ... B:15-168
 - viewing ... B:15-164, B:15-170
- policies, examples of ... B:15-84
- prefix list ... B:15-81
 - applying to an interface ... B:15-83
 - discarding or allowing routes ... B:15-82
 - entry order with ... B:15-82
 - example configuration ... B:15-88
 - filtering routes ... B:15-81
 - load balancing with ... B:15-86
 - naming ... B:15-82
 - network address ... B:15-82
 - prefix length, specifying ... B:15-83
 - prohibiting advertisement of external traffic ... B:15-85
 - troubleshooting ... B:15-167
- remote AS ... B:15-75
- route maps ... B:15-88
 - applying policies to inbound routes ... B:15-104
 - applying to neighbor ... B:15-106
 - communities, deleting ... B:15-105
 - controlling routes neighbor advertises ... B:15-97
 - entry in ... B:15-90
 - filtering inbound routes ... B:15-103
 - load balancing ... B:15-99
 - routes advertised ... B:15-92
- route summaries ... B:15-108
- router ID ... B:15-74
- soft reconfiguration ... B:15-107
- troubleshooting ... B:15-164
 - common problems ... B:15-174

binding

- ADSL interface to ATM ... B:7-28
- ATM subinterface to PPP interface ... B:7-34, B:7-39
- multiple carrier lines to Frame Relay interface ... A:2-10
- multiple carrier lines to PPP interface ... A:2-7
- physical interface to Frame Relay interface ... B:6-36
- physical interface to HDLC interface ... B:6-44
- physical interface to PPP interface ... B:6-10

Boink attack ... A:4-9

Bonk attack ... A:4-9

boot

- code ... B:1-30
- updating ... B:1-60
- error messages ... A:1-26, A:1-27

bootstrap mode context ... B:1-67

- commands ... B:1-68

bootup process ... B:1-30

Border Gateway Protocol

See BGP

BRI backup interface

demand routing

- activating ... A:3-42
- caller ID ... A:3-43
- configuring ... A:3-38
- LDN for BRI S/T ... A:3-40
- resource pool member ... A:3-42
- SPID for BRI U ... A:3-41
- switch type ... A:3-39

line status ... A:3-74

persistent backup connection

- activating interface ... A:3-51
- bonding channels ... A:3-52, A:3-66
- caller ID ... A:3-55
- configuring ... A:3-49
- LDN for BRI S/T ... A:3-50
- SPID for BRI U ... A:3-51
- switch type ... A:3-50

See also BRI primary interface

test calls ... A:3-85

troubleshooting ... A:3-72

BRI interface

- configuring through Web browser interface ... B:14-90
- troubleshooting through Web browser interface ... B:14-92

BRI ISDN

local loop ... B:8-5, A:3-7

BRI primary interface

- accessing ... B:8-40
- activating ... B:8-43
- assigning to ISDN group ... B:8-44
- caller ID options ... B:8-43
- configuring ... B:8-40
- LDN for BRI S/T module ... B:8-43
- line maintenance ... B:8-77
- See also* BRI backup interface
- signaling (switch) type ... B:8-41
- SPID and LDN for BRI U module ... B:8-42
- test calls ... B:8-75
- troubleshooting ... B:8-71
- viewing status of ... B:8-65

bridge table ... B:10-5, B:10-11

viewing ... B:10-8, B:10-9

bridging

- bridge group configuration ... B:10-6, B:10-7
- configuring ... B:10-5
- interfaces ... B:10-7
- IP addresses with ... B:10-7
- overview ... B:10-3
- protocol ... B:10-4, B:10-6
- QoS ... A:8-26, A:8-41, A:8-50
- remote ... B:10-3
- disabling IP routing ... B:10-7, B:10-10
- merging remote networks ... B:10-4

table

See bridge table

troubleshooting ... B:10-10

valid interfaces ... B:10-6

broadband network, regional ... B:7-7

C

CA

- certificate ... A:10-56
- loading ... A:10-58
- profile ... A:10-57, A:10-58
- role in IKE authentication ... A:10-10
- SCEP ... A:10-56, A:10-57
- selecting ... A:10-55
- submitting self certificate request to ... A:10-59

- cable
 - 100Base-T ... B:3-2
 - 10Base-T ... B:3-2
 - crossover ... B:9-14
 - EIA 530 ... B:5-11
 - for DSX-1 ... B:9-14
 - for G.703 ... B:9-5
 - serial ... B:1-10, B:1-14
 - UTP for E1 or T1 connection ... B:4-7
 - UTP ribbon ... B:7-12
 - V.35 ... B:5-9
 - X.21 ... B:5-10
- call
 - ISDN, setup process ... B:8-12
- caller ID
 - caller-number ... B:8-38, A:3-37
 - overriding ... B:8-43, A:3-43
- CBWFQ ... A:8-11, A:8-19
 - bandwidth allocating ... A:8-26, A:8-28
 - class defining ... A:8-21
 - bridged traffic ... A:8-26
 - IP header ... A:8-23
 - RTP ... A:8-26
 - ToS value ... A:8-21
 - UDP port ... A:8-25
 - example configuration ... A:8-30
 - percent versus remaining percent ... A:8-28, A:8-59, A:8-72
 - with multilinks ... A:8-29
- central office
 - See* CO
- certificate authority
 - See* CA
- certificate revocation list
 - See* CRL
- Challenge Handshake Authentication Protocol
 - See* CHAP
- Channel Service Unit/Digital Service Unit
 - See* CSU/DSU
- channels
 - E1- and T1-carrier lines ... B:4-13
 - FDL, for T1 interface ... B:4-20
 - for E1 interface ... B:4-14
 - for ISDN ... B:8-4
 - for T1 interface ... B:4-14
- CHAP
 - example configuration ... B:6-52
 - for backup interfaces ... A:3-44
 - for primary ISDN interfaces ... B:8-53
 - hashing ... B:6-12
 - password ... B:6-14, B:6-15
 - password, case-sensitive ... B:6-65
 - troubleshooting ... B:6-65
 - username (hostname) ... B:6-13, B:6-15
 - username, case-sensitive ... B:6-65
- Chargen attack ... A:4-9
- CIDR
 - DHCP pool ... B:13-8, B:13-9
 - IP address for ATM subinterface ... B:7-21
 - IP address for Frame Relay subinterface ... B:6-29
 - IP address for HDLC interface ... B:6-43
 - IP address for PPP interface ... B:6-8
 - notation ... B:11-6
 - static route ... B:11-14
- CIR
 - Frame Relay ... B:6-19
 - setting ... B:6-35
- class-based weighted fair queuing
 - See* CBWFQ
- CLI ... B:1-5
 - accessing ... B:1-10
 - editing commands ... B:1-65, A:1-14
 - events displayed in ... B:1-51
 - file management using the copy command ... A:1-16
 - help tools ... B:1-65, A:1-13
 - initial access ... A:1-9
 - IP address convention ... B:1-7, A:1-5
 - prompt convention ... B:1-6, A:1-4
 - using to set up Web browser interface
 - access ... B:1-11, A:1-10
- client ID
 - interface as DHCP client ... B:13-24
 - viewing, for DHCP client ... B:13-19
- client-to-site VPN
 - IKE mode config ... A:10-47
 - IKE mode for ... A:10-28
 - NAT-T with ... A:10-31
 - peer ID
 - in crypto map ... A:10-44
 - in IKE policy ... A:10-26
 - in remote ID list ... A:10-34
 - specifying traffic for ... A:10-38, A:10-48
 - Xauth with ... A:10-49

- clock source
 - for E1 interface ... B:4-18
 - for primary BRI interface ... B:8-15
 - for serial interface ... B:5-13
 - for T1 interface ... B:4-18
- CO
 - ADSL distance and service ... B:7-5
 - ADSL infrastructure ... B:7-4
 - local loop ... B:5-4
 - of public carrier ... B:4-4
- commands
 - basic mode ... B:1-39
 - clear commands ... B:1-39, B:1-44
 - clear event-history ... A:4-26
 - clock ... B:1-45
 - configure ... B:1-46
 - copy ... B:1-46, A:1-16
 - do ... B:1-67, A:1-15
 - editing ... B:1-65, A:1-14
 - enable mode ... B:1-43
 - erase ... B:1-50
 - events ... B:1-51
 - exit ... B:1-67, A:1-15
 - global configuration mode ... B:1-61
 - help ... B:1-65, A:1-13
 - no ... B:1-67, A:1-15
 - reload ... B:1-51
 - reload in ... B:1-73
 - show ... A:1-21
 - show event-history ... A:4-26
 - show tech ... B:1-58
 - show, list of ... B:1-51
 - syntax conventions for ... B:1-5
 - write ... B:1-57
- communities
 - BGP ... B:15-97
 - SNMP ... B:2-54
- community list
 - for route map ... B:15-90
- compact flash
 - advantages of booting from ... B:1-32
 - configuring, card ... B:1-33
 - file transfer with ... B:1-83
 - slot location ... B:1-28
 - troubleshooting ... B:1-71
- configuration file
 - editing using a text editor ... B:1-75, A:1-25
 - running-config ... B:1-30
 - startup-config ... B:1-30
 - transfer using
 - compact flash ... B:1-83
 - console port ... B:1-78
 - TFTP ... B:1-80
- connect sequence
 - configuring through Web browser
 - interface ... B:14-98
 - for demand interface ... B:8-30, A:3-28
- connector
 - RJ-11 ... B:7-12, B:8-8
 - RJ-45 ... B:3-2, B:8-8
 - RJ-48C ... B:4-7, B:9-14
- console
 - configuring password through Web browser
 - interface ... B:14-31
 - establishing a terminal session with ... A:1-9
 - file transfer with ... B:1-78
 - password for ... B:2-5
 - port ... B:1-14
 - terminal session with ... B:1-10
- content filtering
 - behavior with unreachable server ... A:7-8
 - buffered Web server responses ... A:7-10
 - configuring ... A:7-5
 - exclusive domains ... A:7-8
 - filter ... A:7-5
 - applying ... A:7-6
 - need for ... A:7-2
 - outstanding requests ... A:7-10
 - router's role in ... A:7-4
 - server
 - integration with ... A:7-3
 - specifying IP address for ... A:7-6
 - troubleshooting ... A:7-11
- context
 - basic mode ... B:1-35, B:1-36
 - bootstrap mode ... B:1-67
 - enable mode ... B:1-35, B:1-36
 - global configuration mode ... B:1-36, B:1-37, B:1-46, B:1-61

- counters
 - clear ACL ... A:5-58
 - clearing Frame Relay counters ... B:6-70
 - clearing interface counters ... B:1-39
 - Frame Relay ... B:6-26, B:6-70
- CRC4 frame format ... B:4-16
- CRL
 - deleting ... A:10-64
 - importing manually ... A:10-61
 - managing ... A:10-64
- crypto map
 - applying to an interface ... A:10-46
 - associating with IKE policy ... A:10-44
 - creating ... A:10-43
 - IKE, configuring with ... A:10-42
 - manual keying
 - configuration tasks ... A:10-65, A:10-67
 - example configuration ... A:10-69
 - setting session key ... A:10-67, A:10-68
 - setting SPI ... A:10-68
 - transform set ... A:10-65, A:10-66
 - peer ID, setting ... A:10-43
 - processed by router ... A:10-20
 - transform set, specifying ... A:10-44
 - viewing ... A:10-71, A:10-86
- CSU
 - external ... B:4-7
 - purpose of ... B:4-5, B:5-5
- CSU/DSU
 - built into router ... B:4-7
 - external ... B:4-7
 - purpose of ... B:1-17, B:4-5, B:5-5
- D**
- D channel
 - ISDN ... B:8-4
 - LAPD transmitted over ... B:8-10
- D4 frame format ... B:4-17
- data communications equipment ... B:6-21
- Data Link Layer
 - ATM ... B:7-17
 - configuring through Web browser interface ... B:14-62
 - for backup ... A:3-11
 - Frame Relay ... B:6-19
 - HDLC ... B:6-40
 - LLDP ... A:14-2
 - PPP ... B:6-6
 - purpose of ... B:4-3, B:5-3
 - Q.921, or LAPD ... B:8-9
 - Q.931 ... B:8-9
- data terminal equipment ... B:6-21
- DCE ... B:6-21
- DE bit ... B:6-36
- debug commands ... B:1-49
 - ADSL ... B:7-48
 - ATM OAM ... B:7-50
 - BGP ... B:15-165
 - crypto ike ... A:10-74
 - crypto ipsec ... A:10-74
 - crypto pki ... A:10-74
 - DHCP client ... B:13-30
 - DHCP server ... B:13-20, B:13-21
 - DNS client ... B:12-14
 - DNS proxy ... B:12-11, B:12-12
 - Ethernet ... B:3-26
 - for content filtering ... A:7-13
 - Frame Relay ... B:6-67, B:6-69, A:2-16
 - HDLC ... B:6-70
 - IKE messages ... A:10-78, A:10-79, A:10-81
 - interface tunnel ... A:11-13
 - ISDN ... B:8-73, A:3-83
 - LLDP ... A:14-9, A:14-11
 - OSPF ... B:15-155
 - PPP ... B:6-61, A:2-13, A:2-15
 - PPP authentication ... B:6-14, B:6-63
 - PPP for PPPoE ... B:7-54
 - PPPoE ... B:7-51
 - probe ... A:9-57
 - RIP ... B:15-153
 - spanning tree ... B:10-25
 - track ... A:9-56
 - viewing through Web browser interface ... B:14-15, A:16-14
 - VPN ... A:10-74
 - VPN debug messages ... A:10-77
- default route
 - configuring ... B:11-17
 - monitoring DHCP route ... A:9-32
 - monitoring negotiated route ... A:9-33
 - receiving from a DHCP server ... B:13-25
 - with dynamic routing ... B:11-18
 - with OSPF ... B:15-38, B:15-54

- demand interface
 - ACL for interesting traffic ... B:8-27, A:3-25
 - ACL to control access to ... B:8-27, A:3-25
 - answer/originate call ... B:8-29, A:3-27
 - called-number ... B:8-39, A:3-37
 - caller-number ... B:8-38, A:3-37
 - configuration summary ... B:8-63, A:3-79
 - configuring through Web browser interface ... B:14-95
 - connect sequence ... B:8-30, A:3-28
 - connect sequence attempts ... B:8-33, A:3-30
 - connect-order ... B:8-32, A:3-30
 - creating ... B:8-23, A:3-22
 - establishing an ISDN call ... B:8-48
 - fast-idle option ... B:8-38, A:3-36
 - hold queue ... B:8-39, A:3-37
 - idle-timeout option ... B:8-37, A:3-36
 - inter-relationship of connect-sequence commands ... B:8-35, A:3-33
 - IP address ... B:8-24, A:3-22
 - MLPPP ... B:8-50
 - MLPPP fragmentation ... B:8-52
 - MLPPP interleave ... B:8-51
 - MTU ... B:8-57, A:3-48
 - PPP authentication ... B:8-54, A:3-44
 - recovery state ... B:8-33, A:3-31
 - resource pool ... B:8-30, A:3-28
 - spoofing up state ... B:8-22, A:3-23
 - static route ... B:8-46
 - static route, floating ... A:3-43
 - troubleshooting ... B:8-70, A:3-81
 - viewing information about ... B:8-61, A:3-82
 - viewing resource pool ... B:8-68, A:3-80
 - viewing running-config for ... B:8-68, A:3-81
- demand routing
 - backup connections
 - configuring ... A:3-18
 - connection instructions ... A:3-33
 - example ... A:3-13, A:3-16
 - initiating ... A:3-12
 - primary ISDN modules ... B:8-16
 - configuration steps ... B:8-18
 - connection instructions ... B:8-30
 - example ... B:8-53
 - initiating ... B:8-26
 - ISDN groups ... B:8-44
 - viewing sessions ... B:8-67, A:3-80
- demarc
 - carrier line ... B:4-5
 - ISDN connections ... B:8-7, A:3-7
 - location for carrier lines ... B:5-5
- demultiplexing channels ... B:4-13
- Denial of Service attack ... A:4-16
- designated router
 - See* OSPF, DR
- DHCP
 - client
 - See* DHCP client
 - configuring through Web browser interface ... B:14-126
 - excluded addresses ... B:13-7, B:13-18
 - network monitoring ... B:13-26
 - overview ... B:13-3
 - pool
 - See* DHCP pool
 - relay ... B:13-6, B:13-32
 - request process ... B:13-3, B:13-4, B:13-20
 - scope for VLAN ... B:13-5, B:13-16
 - server
 - See* DHCP server ... B:13-4
- DHCP client
 - ATM subinterface as ... B:7-21
 - Ethernet interface as ... B:3-5
 - Frame Relay subinterface as ... B:6-29
 - interface as ... B:13-5
 - activating ... B:13-22, B:13-23
 - administrative distance ... B:13-27
 - attaching network monitoring track ... B:13-26
 - client ID ... B:13-24
 - hostname for ... B:12-17
 - receiving optional configurations ... B:13-22, B:13-25
 - releasing address ... B:13-29
 - renewing address ... B:13-29
 - troubleshooting ... B:13-28, B:13-30
 - valid interfaces ... B:13-6
 - viewing lease ... B:13-28
 - monitoring default route ... A:9-32
 - viewing connected clients ... B:13-19

- DHCP pool
 - child ... B:13-13
 - creating ... B:13-7
 - default gateway ... B:13-9
 - example configuration ... B:13-14
 - lease time ... B:13-10
 - multiple ... B:13-8
 - network address ... B:13-8
 - parent ... B:13-13
 - single fixed address ... B:13-14, B:13-21
 - VLAN ... B:13-15
- DHCP server
 - client names in host table ... B:12-9
 - configuring router as ... B:13-5, B:13-6
 - functions ... B:13-3
 - ping settings ... B:13-17, B:13-18
 - troubleshooting ... B:13-19
 - viewing client bindings ... B:13-19, B:13-20
- Diffie-Hellman key
 - automatic generation with IKE ... A:10-9, A:10-64
 - key lengths ... A:10-67
 - PFS group for ... A:10-46
 - specifying group for IKE SA ... A:10-24, A:10-29
- DiffServ ... A:8-5, A:8-7, A:8-10
 - AF mapping ... A:8-9
 - CBWFQ classes ... A:8-10, A:8-21
 - DSCP marking ... A:8-10, A:8-45, A:8-50
 - See also* packet marking
 - IP precedence mapping ... A:8-8, A:8-10, A:8-17
 - LLQ values ... A:8-10, A:8-38
 - WFQ mapping ... A:8-10, A:8-16, A:8-17
- digital certificate
 - advantages ... A:10-55
 - CA certificate ... A:10-56
 - configuring with Web browser
 - interface ... A:16-123
 - CRL ... A:10-64
 - deleting ... A:10-63
 - keys used with ... A:10-10
 - loading CA certificate ... A:10-59
 - obtaining automatically ... A:10-57, A:10-59
 - obtaining manually
 - configuring profile ... A:10-58
 - importing self certificate ... A:10-61
 - loading CA certificate ... A:10-59
 - requesting self certificate ... A:10-60
 - overview ... A:10-54
 - peer ID for peer that uses ... A:10-34
 - standards ... A:10-29, A:10-55
 - viewing ... A:10-62
 - See also* CA and CRL
- digital signal zero ... B:4-13
- Digital Subscriber Line
 - See* DSL
- Discard Eligible Bit ... B:6-36
- DLCI ... B:6-22
 - assigning to Frame Relay subinterface ... B:6-28
- DNS ... B:12-8
 - client
 - enabling ... B:12-8
 - functions ... B:12-5
 - troubleshooting ... B:12-14
 - configuration tasks ... B:12-8
 - host table ... B:12-3
 - See* host table
 - overview ... B:12-3
 - proxy
 - See* DNS proxy
 - server
 - See* DNS server
 - support on ProCurve Secure Router ... B:12-5
- DNS proxy ... B:12-8
 - default domain name for ... B:12-9
 - enabling ... B:12-10
 - external DNS server for ... B:12-10
 - troubleshooting ... B:12-11, B:12-12
- DNS server ... B:12-3
 - configuring through Web browser
 - interface ... B:14-121
 - external, specifying ... B:12-10, B:12-13
 - in DHCP pool ... B:13-11
 - in IKE mode config pool ... A:10-48
 - receiving from a DHCP server ... B:13-25, B:13-28
 - router as ... B:12-10
 - See also* DNS proxy
- do command ... B:1-67
- domain name
 - default ... B:12-9
 - definition ... B:12-3
 - DHCP pool, in ... B:13-12
- DR
 - See* OSPF, DR
 - See* PIM-SM, DR

- drop-and-insert module
 - description of ... B:9-3
- DSX-1 interface
 - assigning channels to T1 interface ... B:9-14
 - setting clock source on T1 interface ... B:9-16
 - viewing configuration of ... B:9-21
- DSX-1 module
 - physical connection ... B:9-14
 - supported standards ... B:9-3
- G.703 interface
 - assigning channels to E1 interface ... B:9-5
 - setting clock source on E1 interface ... B:9-7
 - viewing configuration of ... B:9-11
- G.703 module
 - physical connection ... B:9-4
 - supported standards ... B:9-3
- DS0 ... B:4-13
- DSCP
 - See* DiffServ
- DSL
 - description of ... B:7-4
 - types of ... B:7-4
- DSL access multiplexer
 - See* DSLAM
- DSLAM ... B:7-7, B:7-9
 - RBE ... B:7-40
 - training phase with ADSL interface ... B:7-13
- DSU
 - built into router ... B:4-7
 - purpose of ... B:4-5, B:5-5
- DSX-1 interface
 - accessing ... B:9-17
 - activating ... B:9-20
 - checking the status of ... B:9-20
 - configuring ... B:9-14
 - frame format ... B:9-18
 - line coding ... B:9-17
 - line length ... B:9-19
 - signaling mode ... B:9-19
 - configuring through Web browser interface ... B:14-105
 - T1 interface
 - assigning channels ... B:9-14
 - setting the clock source ... B:9-16

- troubleshooting
 - accruing errored seconds and clock slips ... B:9-22
 - alarms or errors that will not clear ... B:9-21
 - yellow alarm ... B:9-22
- DSX-1 module
 - physical connection to ... B:9-14
 - standards supported ... B:9-4
- DTE ... B:6-21
- duplex setting
 - for Ethernet interface ... B:3-11
- dynamic DNS ... B:12-15, B:13-27
 - activating the client ... B:12-16, B:12-17
 - configuration tasks ... B:12-16
 - overview ... B:12-6, B:12-15
 - services
 - Custom DNS ... B:12-7, B:12-16, B:12-17, B:12-18
 - Dynamic DNS ... B:12-6, B:12-16
 - Static DNS ... B:12-7, B:12-17

E

- E1 + G.703
 - See* G.703 interface and drop-and-insert module
- E1 frame format ... B:4-16
- E1 interface
 - activating ... B:4-21
 - binding
 - to Frame Relay interface ... B:6-37
 - to HDLC interface ... B:6-44
 - to PPP interface ... B:6-11
 - channels for ... B:4-14
 - clock source ... B:4-18
 - configuration mode context for ... B:4-11
 - configuring through CLI ... B:4-10
 - configuring through Web browser interface ... B:14-54
 - Data Link Layer
 - Frame Relay ... B:6-23
 - HDLC ... B:6-40
 - PPP ... B:6-6
 - example Frame Relay configuration ... B:6-48
 - example PPP configuration ... B:6-48
 - frame format ... B:4-16
 - interface range command ... B:4-12
 - line coding ... B:4-15
 - line errors ... B:4-23

- port number ... B:4-11
- slot number ... B:4-11
- speed for channel ... B:4-15
- threshold commands ... B:4-23
- troubleshooting ... B:4-31
- viewing configuration of ... B:4-29
- viewing status of ... B:4-27
- E1 module
 - standards supported ... B:4-8
 - with built-in DSU ... B:4-8
- E1-carrier line
 - 2.048 Mbps bandwidth ... B:4-3
 - 32 channels ... B:4-13
 - analog voice on ... B:4-3
 - elements of ... B:4-3
 - external CSU ... B:4-7
 - for analog voice ... B:9-3
 - local loop ... B:4-4
 - serial interface for ... B:5-3
 - with G.703 interface ... B:9-3
- eBGP multihop ... B:15-78
- EIA 530 cable ... B:5-11
- enable mode context ... B:1-36
 - AAA named list for ... B:2-18
 - clear commands ... B:1-44
 - commands ... B:1-43
 - configuring password through Web browser interface ... B:14-28
 - password ... B:2-4
 - show commands ... B:1-51
- encryption
 - See also* ESP
 - specifying algorithms for ... A:10-40
 - with IPSec ... A:10-6
- encryption algorithm
 - definition of ... A:10-6
 - for IKE SA ... A:10-29
 - for IPSec SA ... A:10-41
 - minimum key lengths for ... A:10-67
- error message
 - AutoSynch™ ... B:1-71
 - bootup ... B:1-76, B:1-77, A:1-26
 - DSX-1 ... B:9-21
 - Ethernet ... B:3-25, B:3-26
 - for serial interface ... B:5-15
 - for unsupported commands ... B:1-39
 - G.703 ... B:9-12
 - logging priority ... A:4-26, A:4-30
 - SafeMode ... B:1-63, A:1-23
 - thresholds for E1 ... B:4-23
 - thresholds for T1 ... B:4-23
- ESF frame format ... B:4-17
- ESP
 - authenticating a packet ... A:10-6
 - default algorithms (VPN Wizard) ... A:10-87
 - encrypting a packet ... A:10-6
 - finding algorithm used by peer ... A:10-83
 - header ... A:10-5
 - manually defining key for ... A:10-67, A:10-68
 - specifying algorithm for ... A:10-41, A:10-65
 - with NAT-T ... A:10-32
 - without encryption ... A:10-42
- et-clock setting ... B:5-13
- Ethernet frame
 - setting maximum size of ... B:3-12
- Ethernet interface
 - accessing ... B:3-3
 - activating ... B:3-4
 - as DHCP client ... B:3-5
 - configuring through CLI ... B:3-3
 - configuring through Web browser interface ... B:14-40
 - debug commands ... B:3-26
 - description for ... B:3-13
 - duplex settings ... B:3-12
 - IP address ... B:3-5
 - MTU ... B:3-12
 - network monitoring ... B:3-8
 - speed settings ... B:3-11
 - subinterface
 - for VLANs ... B:3-19
 - IP address ... B:3-20
 - viewing configurations for ... B:3-22
 - viewing status of ... B:3-20
 - VLAN ID ... B:3-19
 - summary of settings ... B:3-14
 - troubleshooting ... B:3-25
 - unnumbered interface ... B:3-10
 - viewing configuration of ... B:3-22
 - viewing status of ... B:3-20
 - VLAN support ... B:3-16

- Ethernet ports
 - auto MDIX ... B:3-2
 - connection speeds ... B:1-15
 - LED ... B:1-26
 - number of ... B:1-15, B:3-2
 - slot number ... B:3-3
- event-history, displaying ... B:3-26
- events
 - displaying ... B:1-51
 - logging ... A:4-12, A:16-30
 - messages, disabling ... B:3-4
- exit command ... B:1-67
- extended authentication
 - See* Xauth

F

- fair queuing
 - See* WFQ
- fast caching ... B:11-12, B:11-22, A:8-10
 - disabled ... B:11-23
 - disabled with PBR ... B:15-127
- FDL channel ... B:4-20
- FIFO ... A:8-10, A:8-11, A:8-17, A:8-32
 - packet threshold ... A:8-18
- file management
- file management
 - copy command ... B:1-46
 - erase command ... B:1-50
 - with Web browser interface ... B:14-9, A:16-8
 - write command ... B:1-57
- firewall
 - ALGs, configuring ... A:4-18
 - application-level gateway ... A:4-7, A:4-9
 - attack checking ... A:4-6, A:4-9, A:4-14
 - blocking attacks ... A:4-9
 - circuit-level gateway ... A:4-8
 - as proxy server ... A:4-6
 - explained ... A:4-6
 - illustration of ... A:4-7
 - configuring with Web browser interface ... A:16-27
 - enabling ... A:4-14
 - packet-filtering ... A:4-8
 - definition of ... A:4-4
 - illustration of ... A:4-5
 - purpose of ... A:4-3
 - reflexive traffic check ... A:4-16
 - stateful-inspection ... A:4-4, A:4-6, A:4-8
 - timeouts ... A:4-21
 - stealth mode ... A:4-17
 - SYN-flood attack check ... A:4-16
 - WinNuke attack check ... A:4-15
 - wizard ... A:16-37
- firmware
 - management of ... B:1-46
- floating static route ... B:11-16
- Fraggle attack ... A:4-9
- frame
 - 802 Slow Protocol ... A:14-3
 - Frame Relay ... A:8-53
 - fragmentation ... A:8-54, A:8-57, A:8-68, A:8-72
 - header size ... A:8-35
 - GRE ... A:11-2
 - headers ... A:8-33, A:8-36
 - IP ... A:11-2
 - IP header ... A:8-6, A:8-20, A:8-23, A:8-35
 - RTP compression ... A:8-35
 - LAPD ... B:8-10
 - LLDP ... A:14-3
 - MLFR
 - flag ... A:8-35
 - header ... A:8-35, A:8-68
 - MLPPP
 - flag ... A:8-35
 - header ... A:8-35
 - PPPoE ... B:7-30
 - PADI ... B:7-31
 - PADO ... B:7-31
 - PADR ... B:7-31
 - PADS ... B:7-32
 - QoS frames per second ... A:8-34
 - RTP header ... A:8-35
 - UDP header ... A:8-35
 - VoIP ... A:8-54, A:8-61, A:8-64
- frame format
 - CRC4 ... B:4-16
 - D4 ... B:4-17
 - E1 ... B:4-16
 - E1 interface ... B:4-16
 - ESF ... B:4-17
 - T1 interface ... B:4-17

- Frame Relay ... B:6-19
 - Be ... A:8-55, A:8-56
 - CIR ... B:6-19, A:8-55, A:8-56
 - DCE ... B:6-21
 - DE ... A:8-56
 - DLCI ... B:6-22
 - DTE ... B:6-21
 - EIR ... A:8-56
 - FRF.12 ... A:2-8, A:8-5, A:8-12, A:8-53, A:8-56
 - See also* Frame Relay fragmentation
 - LMI ... B:6-23
 - network components ... B:6-21
 - NNI ... B:6-21
 - PVC ... B:6-20, A:8-53
 - PVC endpoint ... B:6-22
 - rate limiting ... A:8-53, A:8-54
 - SLA ... B:6-19, B:6-35
 - UNI ... B:6-21
 - VoIP QoS ... A:8-53
- Frame Relay fragmentation ... A:8-12, A:8-35, A:8-53, A:8-54, A:8-56
 - configuring ... A:8-68
 - fragment size ... A:8-56
 - packet header size ... A:8-35
- Frame Relay interface
 - activating ... B:6-25
 - binding to physical interface ... B:6-36
 - configuring through CLI ... B:6-23
 - configuring through Web browser
 - interface ... B:14-68
 - counters ... B:6-26
 - debug commands ... B:6-67
 - example configuration ... B:6-48, B:6-50
 - LMI statistics ... B:6-67
 - show commands ... B:6-54, B:6-67
 - signaling role ... B:6-25
 - signaling type ... B:6-26
- subinterface
 - as a DHCP client ... B:6-29
 - CIR ... B:6-35
 - creating ... B:6-28
 - DE bit ... B:6-36
 - description ... B:6-38
 - DLCI for ... B:6-28
 - EIR ... B:6-35
 - IP address ... B:6-29
 - MTU ... B:6-38
 - network monitoring ... B:6-32
 - secondary IP address ... B:6-37
 - unnumbered interface ... B:6-33
- summary of main settings ... B:6-24
- troubleshooting ... B:6-66, A:2-13
 - clearing counters ... B:6-70
 - LMI messages ... B:6-69
 - LMI statistics ... B:6-67
 - PVC status ... B:6-68
- FRF.12
 - See* Frame Relay fragmentation
- FTP
 - ACL to control access ... A:5-21
 - ALG for ... A:4-19
 - configuring password through Web browser
 - interface ... B:14-27, B:14-34
 - controlling, access ... B:2-13
 - local user list ... B:2-11
 - traffic through a firewall ... A:4-5
- FTP server
 - enabling through the Web browser
 - interface ... B:14-22, A:16-20
 - enabling, on router ... B:1-85
 - troubleshooting ... B:1-85
- full-duplex
 - Ethernet interface settings ... B:3-12

G

- G.703 interface
 - accessing ... B:9-7
 - activating ... B:9-10
 - checking the status of ... B:9-10
 - configuring ... B:9-4
 - frame format ... B:9-8
 - line coding ... B:9-7
 - TS16 ... B:9-9
 - configuring through Web browser interface ... B:14-105
 - E1 interface
 - assigning channels ... B:9-5
 - setting clock source ... B:9-7
 - show commands ... B:9-10
 - troubleshooting ... B:9-12
 - accruing errored seconds and clock slips ... B:9-13
 - alarms or errors that will not clear ... B:9-12
 - yellow alarm ... B:9-13
 - TS16 ... B:9-9
- G.703 module
 - physical connection ... B:9-4
 - standards supported ... B:9-4
 - G.lite ... B:7-10
 - gateway
 - application-level ... A:4-7
 - circuit-level ... A:4-6
 - Generic Routing Encapsulation
 - See* GRE
 - global configuration mode context ... B:1-37
 - commands ... B:1-61
 - interface configuration mode context ... B:1-37
 - line configuration mode context ... B:1-38
 - router configuration mode context ... B:1-38
 - GRE ... A:11-2
 - advantages and disadvantages of ... A:10-13
 - checksum verification ... A:11-12
 - encapsulation ... A:11-5
 - tunnel configuration ... A:11-4, A:11-5, A:11-7
 - See also* tunnel
 - tunneling ... A:11-5
 - advantages and disadvantages of ... A:11-3
 - multicasts ... A:11-9
 - routing updates ... A:11-8
 - VPN overlay ... A:10-13

H

- H.323 ... A:8-36, A:8-62, A:8-66
 - ALG for ... A:4-19
- half-duplex
 - Ethernet interface settings ... B:3-12
- hash algorithm
 - definition ... A:10-6
 - for IKE SA ... A:10-29
 - for IPSec SA ... A:10-41
 - key length for ... A:10-67
- HDLC
 - ABM ... B:6-40
 - ARM ... B:6-40
 - NRM ... B:6-40
- HDLC interface
 - activating ... B:6-42
 - binding to physical interface ... B:6-44
 - configuring through CLI ... B:6-40
 - configuring through Web browser interface ... B:14-74
 - description ... B:6-46
 - example configuration ... B:6-50
 - IP address ... B:6-42
 - MTU ... B:6-45
 - secondary IP address ... B:6-45
 - show commands ... B:6-54
 - troubleshooting ... B:6-70
 - unnumbered interface ... B:6-43
- HDSL ... B:7-4
- help
 - ? command ... B:1-65
 - tools for CLI ... B:1-65, A:1-13
- helper address
 - for UDP forwarding ... B:13-32
- high-priority queuing
 - See* LLQ
- host table
 - adding an entry ... B:12-9, B:12-13
 - altering an entry ... B:12-13
 - dynamic hosts, adding ... B:12-9
 - queries to ... B:12-10, B:12-12

- hostname
 - adding to local table ... B:12-9
 - definition ... B:12-3
 - interface ... B:12-17, B:13-25
 - LLDP message, in ... A:14-4
 - preventing LLDP advertisement of ... A:14-13
 - setting router hostname ... B:1-61
 - static hostname with dynamic address ... B:13-27
 - See also* dynamic DNS
 - viewing neighbors' ... A:14-5
 - wildcard ... B:12-16
- HTTP request probe ... A:9-12, A:9-20
 - See also* network monitor probe
- HTTP server
 - ACL to control access ... A:5-22
 - enabling ... B:2-11
 - enabling through Web browser interface ... B:14-22, A:16-20
 - local user list ... B:2-11
 - monitoring a remote server ... A:9-20
- HTTPS server
 - enabling ... B:2-11
 - enabling through web browser interface ... B:14-22, A:16-20
 - local user list ... B:2-11

I

- ICMP
 - flood ... A:4-9
 - session timeout ... A:4-21
- ICMP echo probe ... A:9-11, A:9-18
 - See also* network monitor probe
- IEEE
 - bridging support ... B:10-4, B:10-6
 - See also* bridging
- IEEE 802.1Q standard ... B:3-16
- IEEE 802.1w
 - See* RSTP
- IEEE 802.D
 - See* STP

- IGMP ... A:12-7, A:12-8, A:12-9
 - downstream interface ... A:12-9, A:12-13, A:12-14, A:12-23, A:12-24
 - enabling on interface ... A:13-29
 - interval ... A:12-19
 - multicasting agent
 - configuring ... A:12-14
 - description ... A:12-6
 - proxy ... A:12-9, A:12-10, A:12-15, A:12-24
 - enabling on downstream interface ... A:12-15
 - query
 - altering interval ... A:12-19
 - description ... A:12-7
 - report ... A:12-7
 - show commands ... A:12-22
 - troubleshooting ... A:12-21
 - upstream interface ... A:12-13, A:12-16
 - version ... A:12-8, A:12-14, A:12-24
- IKE
 - advantages ... A:10-64
 - authentication information, needed for ... A:10-19
 - authentication methods ... A:10-10
 - Diffie-Hellman key generation ... A:10-9
 - monitoring ... A:10-76, A:10-78
 - phase 2 ... A:10-84
 - negotiating IPSec SA ... A:10-8
 - phase 1
 - description of ... A:10-8
 - monitoring ... A:10-77
 - security proposals ... A:10-29
 - settings for ... A:10-12, A:10-15
 - phase 2
 - description of ... A:10-12
 - monitoring ... A:10-78
 - settings for ... A:10-13, A:10-16
 - troubleshooting ... A:10-78, A:10-79
 - comparing IKE policies ... A:10-80, A:10-82
 - comparing IPSec policies ... A:10-82
 - viewing peer's IPSec policies ... A:10-83
 - viewing security parameters ... A:10-81
 - Xauth
 - See* Xauth
- IKE attribute policy
 - configuring ... A:10-28, A:10-29

- IKE mode ... A:10-26
 - aggressive
 - definition ... A:10-11
 - specifying ... A:10-27
 - default ... A:10-26
 - initiate, specifying ... A:10-27
 - main ... A:10-34
 - definition ... A:10-11
 - specifying ... A:10-27
 - with client-to-site VPN ... A:10-28, A:10-34
 - respond, specifying ... A:10-27
- IKE mode config
 - applying pool to IKE policy ... A:10-49
 - pool configuration ... A:10-48
 - viewing a pool ... A:10-71
- IKE policy
 - compatibility with peer ... A:10-80
 - configuring ... A:10-23, A:10-24
 - default ... A:10-26
 - example configuration ... A:10-29, A:10-30
 - for multiple peers ... A:10-25
 - peer ID ... A:10-24
 - processed by router ... A:10-20
 - viewing ... A:10-71
- IKE SA
 - clearing ... A:10-71
 - compatibility with peer ... A:10-80, A:10-82
 - configuring security parameters for ... A:10-23
 - default settings ... A:10-16, A:10-29
 - definition ... A:10-8
 - lifetime ... A:10-29
 - security parameters for ... A:10-15, A:10-29
 - specifying peer ID ... A:10-24
 - viewing ... A:10-70
- interesting traffic
 - defining, for backup with demand routing ... A:3-18, A:3-24
 - defining, for demand routing ... B:8-18
- interface
 - ADSL ... B:7-12
 - applying ACL to ... A:5-19
 - assigning a QoS map to ... A:8-28, A:8-44, A:8-51
 - assigning ACP to ... A:5-38
 - ATM ... B:7-17
 - BRI ... B:8-40, A:3-39, A:3-49
 - demand ... B:8-23, A:3-20
 - E1 ... B:4-10, B:9-5
 - G.703 ... B:9-7
 - Ethernet ... B:3-2
 - Frame Relay ... B:6-23
 - HDLC ... B:6-40
 - helper address for UDP applications ... B:13-32
 - loopback
 - tunnel source ... A:11-6
 - modem ... A:3-39, A:3-53
 - numbering convention ... B:1-22
 - passive, with RIP ... B:15-30
 - PPP ... B:6-6, A:8-15
 - PPP, for PPPoE ... B:7-33
 - R, for ISDN ... B:8-9, A:3-9
 - router numbering convention ... A:1-5
 - S, for ISDN ... B:8-8, A:3-9
 - serial ... B:5-3
 - T, for ISDN ... B:8-8, A:3-9
 - T1 ... B:4-10, B:9-14
 - DSX-1 ... B:9-17
 - tunnel ... A:11-4, A:11-13
 - filtering traffic ... A:11-11
 - IGMP ... A:11-9
 - PIM-SM ... A:11-9
 - sending routing updates ... A:11-8
 - U, for ISDN ... B:8-8, A:3-9
- internal flash memory
 - See* memory
- Internet
 - preventing non-work-related use of ... A:7-2
- IP address
 - ACL ... A:8-23, A:8-39, A:8-47
 - ATM subinterface ... B:7-20
 - bridge group ... B:10-7
 - CBWFQ ... A:8-20, A:8-73
 - compared to hostname ... B:12-3
 - definition ... B:11-3
 - demand interface ... A:3-22
 - DHCP subnet ... B:13-8
 - dynamic
 - IKE mode with ... A:10-27
 - interface ... B:13-22
 - releasing and renewing interface's dynamic address ... B:13-29
 - See also* DHCP client
 - See also* dynamic DNS
 - static hostname with ... B:12-6, B:12-15, B:13-27
 - Ethernet interface ... B:3-5
 - Ethernet subinterface ... B:3-20

- excluding from DHCP ... B:13-7
- fixed DHCP address ... B:13-14
- Frame Relay subinterface ... B:6-29
- GRE ... A:11-4
- HDLC interface ... B:6-42
- helper address for UDP packets ... B:13-32
- LLQ ... A:8-37, A:8-39
- network address ... B:11-4
- notation convention ... B:1-7
- PPP backup interface ... A:3-58
- PPP interface ... B:6-8
- PPP interface, for PPPoE ... B:7-34
- QoS map ... A:8-21
- routing according to ... B:11-7
- SIP ... A:8-64
- ToS ... A:8-45, A:8-47
- tunnel ... A:11-4, A:11-7
- VPN peer's, specifying ... A:10-24
- WFQ ... A:8-11, A:8-14
- IP precedence ... A:8-5, A:8-6, A:8-7, A:8-38
 - CBWFQ value ... A:8-7, A:8-21
 - LLQ priority ... A:8-7
 - TOS setting ... A:8-50
 - WFQ value ... A:8-7, A:8-15, A:8-16
- IP Security (IPSec)
 - configuring a VPN using ... A:10-15
 - definition of ... A:10-4
 - Diffie-Hellman key
 - key length ... A:10-67
 - specifying group for ... A:10-46
 - encryption algorithm
 - purpose ... A:10-6
 - specifying ... A:10-40
 - hash algorithm
 - purpose ... A:10-6
 - specifying ... A:10-40
 - header ... A:10-5
 - IKE with ... A:10-8
 - mode
 - specifying ... A:10-42
 - transport ... A:10-5
 - tunnel ... A:10-5
 - module for ... A:10-14
 - protocols ... A:10-5
 - See also* AH and ESP
 - See also* VPN, crypto map, IKE, and transform set
 - VPN tunnel ... A:10-7
- IP spoofing attack ... A:4-9

- IPSec SA
 - clearing ... A:10-71
 - configuring with IKE
 - advantages ... A:10-8
 - tasks ... A:10-15, A:10-23
 - definition of ... A:10-7
 - manual keying
 - crypto map configuration ... A:10-65, A:10-67
 - example configuration ... A:10-69
 - key length ... A:10-67
 - other crypto map configurations ... A:10-68
 - setting session key ... A:10-67, A:10-68
 - setting SPI ... A:10-68
 - transform set ... A:10-65, A:10-66
 - security parameters
 - compatibility with peer ... A:10-82
 - configuring ... A:10-40
 - configuring in crypto map ... A:10-44, A:10-45
 - configuring in transform set ... A:10-40
 - default settings ... A:10-87
 - finding peer's using debug
 - commands ... A:10-83
 - overview ... A:10-16
 - viewing ... A:10-85
 - viewing ... A:10-71
- ISDN
 - and ADSL ... B:7-9
 - backup methods using ... A:3-11
 - BRI transmission rates ... B:8-4, A:3-9
 - call setup ... B:8-12
 - channels ... B:8-4, A:3-6
 - characteristics of ... B:8-4, A:3-5
 - configuring through Web browser
 - interface ... B:14-88
 - Data Link Layer ... B:8-9, A:3-12, A:3-57
 - elements of, connection ... B:8-5, A:3-7
 - establishing a connection ... B:8-36
 - line coding for BRI ... B:8-9
 - PRI ... B:8-4
 - R interface ... B:8-9, A:3-9
 - S interface ... B:8-8, A:3-9
 - switch ... B:8-7, A:3-7
 - switch type for ... B:8-41, A:3-40
 - T interface ... B:8-8, A:3-9
 - U interface ... B:8-8, A:3-9
 - ISDN backup module
 - BRI S/T ... A:3-9
 - BRI U ... A:3-9

- ISDN group
 - assigning BRI interface to ... B:8-44
 - assigning to resource pool ... B:8-45
 - configuring ... B:8-44
 - configuring through Web browser interface ... B:14-93
 - creating ... B:8-44
- ISDN primary module
 - BRI S/T ... B:8-15
 - BRI U ... B:8-15
 - supported standards ... B:8-15
- J**
- J1-carrier line ... B:4-3
- Jolt attack ... A:4-9
- Jolt2 attack ... A:4-9
- K**
- key
 - definition of ... A:10-6
 - manually specifying for VPN tunnel ... A:10-68
- L**
- LAN
 - connecting router to ... B:3-2
- Land attack ... A:4-9
- LAPD ... B:8-10
 - frames ... B:8-10
- LBO, setting, for T1 interfaces ... B:4-19
- LDN
 - backup ISDN connection (demand routing) ... A:3-40
 - persistent backup connections ... A:3-50
 - primary ISDN modules ... B:8-43
 - viewing LDN for peer ... A:3-89
- LED
 - backup ... B:1-25, A:3-73
 - Ethernet ... B:1-26
 - fault ... B:1-23
 - power ... B:1-23
 - Stat ... B:1-24
 - troubleshooting E1 or T1 interface using ... B:4-32
 - troubleshooting serial interface using ... B:5-18
 - Tx and Rx ... B:1-25
 - wide slot ... B:1-25
- Line Build Out ... B:4-19
- line coding
 - for E1 interface ... B:4-15
 - for T1 interface ... B:4-16
- Link Management Interface ... B:6-23
- link state advertisement
 - See* OSPF, LSA
- LLDP ... A:14-2
 - detailed information, viewing ... A:14-6
 - enabling and disabling ... A:14-12, A:14-13
 - frame format ... A:14-3
 - message
 - information in ... A:14-3
 - monitoring ... A:14-9
 - viewing complete ... A:14-10
 - neighbor, viewing ... A:14-5, A:14-7
 - timers
 - setting ... A:14-14
 - viewing ... A:14-11
- LLQ ... A:8-6, A:8-11, A:8-32
 - bandwidth guarantee ... A:8-42, A:8-43
 - bridged traffic ... A:8-41
 - CBWFQ ... A:8-20, A:8-31
 - IP header value ... A:8-39
 - RTP ... A:8-39
 - ToS value ... A:8-38
- LMI ... B:6-23
 - statistics, viewing ... B:6-67
- local loop
 - ADSL ... B:7-7
 - broadband network ... B:7-7
 - DSLAM ... B:7-7
 - splitters ... B:7-9
 - carrier line
 - CSU/DSU ... B:4-5
 - demarc ... B:4-5
 - NIU ... B:4-5
 - office channel unit ... B:4-6
 - repeater ... B:4-6
 - structure of ... B:4-4
 - wire span ... B:4-5
 - demarc ... B:5-5

- ISDN ... B:8-5, A:3-7
 - interfaces for connecting equipment ... B:8-8
 - ISDN switch ... B:8-7, A:3-7
 - NIU ... B:8-7, A:3-8
 - NT1 ... B:8-7, A:3-8
 - NT2 ... B:8-7, A:3-8
 - repeater ... B:8-7, A:3-7
 - TA ... B:8-7, A:3-8
 - TE1 ... B:8-7, A:3-8
 - TE2 ... B:8-7, A:3-8
- serial interface
 - NIU ... B:5-5
 - repeater ... B:5-6
 - structure of ... B:5-4
- local user list ... B:2-11
 - encrypting passwords ... B:2-13
- logging
 - ACP matches ... A:4-27
 - attacks ... A:4-26
 - configuring through Web browser interface ... A:16-30
 - events ... A:4-12, A:4-24
 - forwarding to email address ... A:4-29
 - forwarding to syslog server ... A:4-27
 - network monitor track state ... A:9-29
 - priority level ... A:4-24
- logical interface
 - ATM ... B:7-17
 - demand interface ... B:8-23, A:3-20
 - for persistent backup connection ... A:3-56
 - Frame Relay ... B:6-19
 - HDLC ... B:6-40
 - PPP ... B:6-6
- loopback interface
 - eBGP multihop with ... B:15-78, B:15-168
 - load balancing with ... B:15-77
 - OSPF router ID ... B:15-44
- low-latency queuing
 - See* LLQ
- LSA
 - See* OSPF, LSA

M

- MAC address
 - LLDP message, in ... A:14-4
 - viewing neighbors' ... A:14-5
- management access
 - configuring policies to control ... A:16-53
- match command ... A:8-26
 - dscp ... A:8-46
 - ip rtp ... A:8-39, A:8-49
 - list ... A:8-41, A:8-48
 - match list ... A:8-26
 - protocol bridge ... A:8-42, A:8-50
 - QoS map options ... A:8-21, A:8-38, A:8-74
- memory
 - internal flash size ... B:1-29
 - types of ... B:1-29
- MLFR
 - binding multiple carrier lines to Frame Relay interface ... A:2-10
 - bundle ID ... A:2-11, A:2-18
 - CBWFQ ... A:8-29
 - configuring with Web browser interface ... A:16-26
 - enabling ... A:2-9
 - QoS ... A:8-29, A:8-35, A:8-68
 - per-call bandwidth ... A:8-65
 - troubleshooting ... A:2-16
 - understanding ... A:2-8
- MLPPP
 - binding multiple carrier lines to PPP interface ... A:2-7
 - CBWFQ ... A:8-29
 - configuring ... A:2-4
 - configuring with Web browser interface ... A:16-24
 - enabling ... A:2-6
 - example of, with demand routing ... B:8-52
 - for demand interface ... B:8-50
 - fragmentation ... B:8-52
 - header ... A:2-6
 - interleave ... B:8-51
 - LCP options for ... A:2-5
 - MRRU ... A:2-5, A:2-15
 - QoS ... A:8-29, A:8-35
 - session ... A:2-5
 - troubleshooting ... A:2-15

- modem interface
 - demand routing
 - configuring ... A:3-38
 - countrycode ... A:3-41
 - resource pool-member ... A:3-42
 - persistent backup connections
 - activating interface ... A:3-54
 - countrycode ... A:3-53
 - troubleshooting ... A:3-76
 - using for a console session ... A:3-55
 - module
 - ADSL2+ ... B:1-18
 - ADSL2+ Annex A ... B:7-11
 - ADSL2+ Annex B ... B:7-11
 - backup ... B:1-19
 - installing ... A:3-10
 - standards supported ... A:3-10
 - E1 ... B:1-17, B:4-8
 - E1+G.703 ... B:9-4
 - IPSec VPN ... B:1-27, A:10-14, A:10-23
 - ISDN primary ... B:1-19, B:8-13
 - list of modules ... B:1-16
 - T1 ... B:1-18, B:4-9
 - T1+DSX-1 ... B:9-14
 - wide slot ... B:1-20
 - MPLS
 - used by ISP ... B:15-69
 - MRRU ... A:2-5, A:2-16
 - MTU
 - for demand interface ... B:8-57, A:3-48
 - for Ethernet interface ... B:3-12
 - for Frame Relay subinterface ... B:6-38
 - for HDLC interface ... B:6-45
 - for PPP interface ... B:6-17
 - OSPF concerns with ... B:15-160
 - routing table, in ... B:11-9
 - tunnel keys ... A:11-14
 - multicast routing table
 - (* , G) entry ... A:13-7, A:13-8, A:13-49
 - (S, G) entry ... A:13-8, A:13-11, A:13-13, A:13-49
 - flags ... A:13-49, A:13-50, A:13-52
 - RP-bit ... A:13-50
 - SPT-bit ... A:13-13, A:13-14
 - incoming interface ... A:13-4, A:13-10, A:13-52
 - monitoring ... A:13-48, A:13-51
 - null incoming interface ... A:13-58
 - outgoing interface list ... A:13-4, A:13-53
 - SG entry ... A:13-7
 - multicasting ... A:12-4, A:12-12
 - adding router stack ... A:12-18
 - addresses ... A:12-5
 - applications of ... A:12-3
 - downstream interface
 - configuring ... A:12-14
 - description ... A:12-13
 - enabling IP routing ... A:12-12
 - fixed interface ... A:12-16
 - forwarding, downstream ... A:12-15
 - helper address ... A:12-12, A:12-13, A:12-15, A:12-16, A:12-23, A:12-24, A:12-27
 - setting of ... A:12-12
 - host group ... A:12-5, A:12-7, A:12-18, A:12-23
 - multicast stub routing ... A:12-11
 - route table ... A:12-25
 - routing protocols ... A:12-8
 - show commands ... A:12-22
 - troubleshooting ... A:12-21, A:12-23
 - tunneling traffic through Internet ... A:12-17
 - upstream interface
 - configuring ... A:12-16
 - description ... A:12-13
 - multihoming
 - troubleshooting ... B:15-174
 - with BGP ... B:15-70, B:15-85
 - multi-netted environment ... A:4-16
 - protecting ... A:4-12
 - See also* reflexive traffic ... A:4-16
 - multiplexing channels ... B:4-13
- ## N
- named list
 - accounting ... B:2-28
 - authentication ... B:2-19
 - authorization ... B:2-24, B:2-25
 - NAT
 - ACL ... A:6-8
 - ACP ... A:6-13
 - assign to interface ... A:6-16
 - many-to-one ... A:6-14
 - one-to-one ... A:6-14
 - port translation ... A:6-15
 - compatibility with a VPN ... A:10-31
 - configuring ... A:6-8
 - configuring ACL for many-to-one ... A:6-9
 - many-to-one ... A:6-2

- network monitoring, for ... A:9-37
- one-to-one ... A:6-5
- one-to-one, with port translation ... A:6-6
- policy keyword ... A:9-38
- troubleshooting ... A:6-21
- with PAT ... A:6-3
- NAT Discovery (NAT-D) ... A:10-31
- NAT-Traversal (NAT-T)
 - correct IPSec protocol for ... A:10-32
 - enabling ... A:10-31, A:10-32
 - NAT-D packet ... A:10-31
 - router performance ... A:10-32
 - version ... A:10-32
- neighbors
 - viewing LLDP information ... A:14-5
 - viewing LLDP information, real time ... A:14-8
- Nestea attack ... A:4-9
- network interface unit
 - See* NIU
- network monitor probe
 - activating ... A:9-25
 - definition ... A:9-3
 - destination ... A:9-12
 - HTTP request ... A:9-12
 - absolute path ... A:9-24
 - configuration ... A:9-20
 - raw string ... A:9-24
 - required response ... A:9-23
 - required response status ... A:9-21
 - type ... A:9-21
 - ICMP echo ... A:9-11
 - configuration ... A:9-18
 - data pattern ... A:9-19
 - size ... A:9-18
 - period ... A:9-16
 - See also* network monitor track and network monitoring
 - source address ... A:9-17
 - source port ... A:9-17
 - state ... A:9-5
 - state, effect on track ... A:9-28
 - TCP connect ... A:9-11, A:9-20
 - timeout ... A:9-14
 - tolerance ... A:9-14
 - types ... A:9-11
 - viewing ... A:9-56
- network monitor track
 - action ... A:9-5
 - activating ... A:9-30
 - associating with a route ... A:9-31
 - DHCP default ... A:9-32
 - negotiated default ... A:9-33
 - static ... A:9-31
 - dampening interval ... A:9-28
 - definition ... A:9-5
 - logging changes ... A:9-29
 - probes for ... A:9-27
 - See also* network monitor probe and network monitoring
 - state ... A:9-5, A:9-28
 - viewing ... A:9-55
- network monitoring
 - attaching track to DHCP client ... B:13-26
 - clearing statistics ... A:9-57
 - configuration steps ... A:9-10
 - examples ... A:9-42
 - interfaces, attaching track to
 - ATM ... B:7-24
 - Ethernet ... B:3-8
 - Frame Relay ... B:6-32
 - purposes of ... A:9-6
 - See also* network monitor probe and network monitor track
 - time before probe fails ... A:9-16
 - wizard for configuring ... A:16-75
- Network Termination 1 ... B:8-7, A:3-8
- Network Termination 2 ... B:8-7, A:3-8
- network-to-network interface ... B:6-21
- Newtear attack ... A:4-9
- NIU ... B:5-5
 - carrier line ... B:4-5
 - ISDN connection ... B:8-7, A:3-8
- NNI ... B:6-21
- no command ... B:1-67
- Normal Response Mode ... B:6-40
- NRM ... B:6-40
- NT1 ... B:8-7, A:3-8
- NT2 ... B:8-7, A:3-8
- null interface ... B:11-18

O

OAM

- debug commands for ... B:7-50
- settings ... B:7-27

office channel unit

- carrier line ... B:4-6

Open Shortest Path First

- See* OSPF

Open Systems Interconnection model

- See* OSI model ... B:4-4

Opentear attack ... A:4-9

Operation, administration, and maintenance (OAM)

- See* OAM

OSI model

- circuit-level gateway and ... A:4-6
- displayed ... B:4-4, B:5-4, B:8-5
- layers used in WAN connection ... B:4-4, B:8-5
- packet-filtering firewall and ... A:4-4

OSPF

- ABR ... B:15-34
 - area configuration on ... B:15-45, B:15-53
 - LSAs with ... B:15-37, B:15-38
 - route summaries ... B:15-47
 - troubleshooting ... B:15-162
- advertising a network ... B:15-45, B:15-54, B:15-59
- area ... B:15-34
 - configuration ... B:15-39, B:15-45
 - example configuration ... B:15-35, B:15-40, B:15-41, B:15-52
 - minimizing overhead ... B:15-33
- as an interior gateway protocol ... B:15-7
- ASBR
 - default route ... B:15-54
 - route summaries ... B:15-55
- authentication ... B:15-32, B:15-62
 - problems with ... B:15-161
- compared to RIP and BGP ... B:15-9
- configuration tasks ... B:15-42, B:15-43
- configuring with Web browser
 - interface ... A:16-148
- default administrative distance ... B:15-11
- DR ... B:15-34
 - LSAs with ... B:15-37
 - priority for ... B:15-60
- example configuration ... B:15-64
- intervals ... B:15-60, B:15-62, A:16-156

LSA ... B:15-33, B:15-37

- intervals for ... B:15-61
- types ... B:15-37, B:15-38
- multicast routing, with ... A:13-28
- network backbone or area 0 ... B:15-36, B:15-46
- overview ... B:15-32
- route summaries
 - ABR configuration ... B:15-47, B:15-50
 - advantages of ... B:15-48
 - ASBR configuration ... B:15-55
 - problems with ... B:15-162, B:15-163
- router ID ... B:15-37, B:15-44
- stub area ... B:15-35, B:15-37, B:15-46, B:15-47
- total stub area ... B:15-36, B:15-38, B:15-47
 - LSAs with ... B:15-37
- troubleshooting ... B:15-155, B:15-158, B:15-162
 - problems router ID ... B:15-161

P

packet marking

- example configuration ... A:8-51
- LLQ ... A:8-44
- selecting traffic ... A:8-46
 - bridged traffic ... A:8-50
 - IP header ... A:8-47
 - RTP ... A:8-49
- ToS value setting ... A:8-46, A:8-50

PAP

- clear text ... B:6-12
- example configuration ... B:6-51
- finding peer's password ... B:6-64
- for backup interfaces ... A:3-44
- for primary ISDN interfaces ... B:8-53
- password ... B:6-14
- password, case-sensitive ... B:6-65
- troubleshooting ... B:6-63
- username ... B:6-14
- username, case-sensitive ... B:6-65

password

- CHAP ... B:6-15
- configuring through Web browser
 - interface ... B:14-27
- console ... B:2-5
- enable mode ... B:2-4
- encrypting all ... B:2-13
- local user list ... B:2-11
- PAP ... B:6-14
- Telnet ... B:2-8

- Password Authentication Protocol
 - See* PAP
- PAT
 - with NAT ... A:6-3
- PBR ... B:15-125
 - applying route map to router traffic ... B:15-144
 - assigning route map to interface ... B:15-144
 - configuration examples ... B:15-144
 - default routes ... B:15-140
 - don't fragment bit ... B:15-143
 - implementation
 - application ... B:15-132
 - payload size ... B:15-137
 - source ... B:15-129
 - traffic priority ... B:15-134
 - marking packets with QoS value ... B:15-141
 - network monitoring, for ... A:9-9, A:9-34
 - route map ... B:15-127
 - selecting traffic ... B:15-128
 - setting the routing policy ... B:15-138
 - troubleshooting ... B:15-175
 - uses for ... B:15-125
- PEM ... A:10-59, A:10-61
- perfect forward secrecy
 - See* PFS
- permanent virtual circuit
 - See* PVC
- PFS
 - default setting ... A:10-87
 - specifying group ... A:10-46
- PHB ... A:8-8, A:8-10
 - assured forwarding ... A:8-8, A:8-9, A:8-22, A:8-23
 - class-selector ... A:8-8, B:15-136
 - default ... A:8-8
 - expedited forwarding ... A:8-9, A:8-50
 - IP Precedence ... A:8-8
 - marking traffic ... A:8-47, A:8-50
- Physical Layer
 - of OSI model ... B:4-4
 - of WAN connection ... B:5-3
 - purpose of ... B:8-5
- PIM-SM ... A:13-3
 - asserts ... A:13-26, A:13-27, A:13-58
 - configuration examples ... A:13-40, A:13-45
 - configuration tasks ... A:13-28
- DR ... A:13-3, A:13-14
- DR, viewing ... A:13-55
- enabling on interface ... A:13-29
- IGMP, with ... A:13-8, A:13-29
- join/prunes ... A:13-18, A:13-19, A:13-61
 - periodic ... A:13-24, A:13-38
 - triggered ... A:13-22, A:13-23
- monitoring ... A:13-48, A:13-54, A:13-55, A:13-56, A:13-61
- multi-access networks, special considerations
 - with ... A:13-26, A:13-36, A:13-39
- null incoming interface ... A:13-59
- pruning a connection ... A:13-14, A:13-21, A:13-58
- receiver joins after source ... A:13-16
- register ... A:13-10, A:13-25
- RP
 - See* RP
- RP tree ... A:13-4, A:13-8
 - (* , G) entry, with ... A:13-7
 - joining ... A:13-8, A:13-15
 - using permanently ... A:13-36
- SP tree ... A:13-5, A:13-7
- SP tree, disabling ... A:13-36
- switching to an SP tree ... A:13-9, A:13-23
 - edge router ... A:13-12, A:13-13
 - receiver joins after ... A:13-16
 - threshold for ... A:13-35
 - threshold, viewing ... A:13-55
- timers ... A:13-37, A:13-38, A:13-39, A:13-51
- troubleshooting ... A:13-48, A:13-54, A:13-55, A:13-56, A:13-61
- unicast routing, with ... A:13-7, A:13-28, A:13-32, A:13-60
- ping command ... B:1-36
 - default ... B:1-40
 - extended options ... B:1-40
- ping of death attack ... A:4-9
- ping probe ... A:9-11, A:9-18
 - See also* network monitor probe
- PKI
 - debug command ... A:10-74
 - definition ... A:10-55
- policy-based routing
 - See* PBR

- port number
 - backup modules ... A:3-39, A:3-49
 - E1+G.703 module ... B:9-4
 - Ethernet interface ... B:3-3
 - for ADSL interfaces ... B:7-12
 - for DSX-1 ... B:9-17
 - for G.703 ... B:9-7
 - for serial interface ... B:5-12
 - ISDN interface ... B:8-44
 - T1+DSX-1 module ... B:9-14
- port translation ... A:6-15
- port-mapping table ... A:6-3
- POTS, and ADSL ... B:7-9
- power source, redundant ... B:1-29
- PPP
 - authentication for demand interface ... B:8-53
 - LCP ... A:2-4
 - NCP ... A:2-5
 - phases ... B:6-5, A:2-4
 - See also* PPP Authentication
 - session ... B:6-5
 - suite of protocols ... B:6-4
- PPP authentication ... B:6-11
 - configuring through Web browser interface ... B:14-65
 - demand routing ... A:3-44
 - determining protocol ... B:6-14, B:6-66
 - peer password ... B:6-14
 - peer username ... B:6-14
 - persistent backup connection ... A:3-58
 - See also* PAP and CHAP
 - troubleshooting ... B:6-63
- PPP backup interface
 - configuring ... A:3-57
- PPP interface
 - See also* PPPoA and PPPoE
 - activating ... B:6-10
 - binding physical interface to ... B:6-10
 - bridging ... B:13-6
 - configuring through Web browser interface ... B:14-62
 - creating ... B:6-6
 - debug authentication ... B:6-14
 - debug commands ... B:6-61, A:2-13
 - description for ... B:6-17
 - DHCP client on ... B:13-6
 - example configuration ... B:6-48
 - for PPPoE ... B:7-32
 - IP address ... B:6-8
 - MTU ... B:6-17
 - negotiated IP address ... B:6-8
 - secondary IP address ... B:6-16
 - show commands ... B:6-54
 - summary of settings ... B:6-7
 - troubleshooting ... B:6-59, A:2-13
 - unnumbered interface ... B:6-9
- PPPoA ... B:7-11
 - binding ATM subinterface to PPP interface ... B:7-39
 - configuring ... B:7-38
 - IP address ... B:7-38
 - PPP interface for ... B:7-38
 - troubleshooting PPP ... B:7-53
 - debug commands ... B:7-54
 - understanding ... B:7-36
- PPPoE ... B:7-11
 - binding ATM subinterface to PPP interface ... B:7-34
 - description of ... B:7-29
 - discovery phases ... B:7-30
 - IP address ... B:7-34
 - MTU size ... B:6-17
 - PPP interface for ... B:7-33
 - setting access concentrator name ... B:7-35
 - setting PPPoE service name ... B:7-36
 - show command ... B:7-52
 - troubleshooting ... B:7-51
 - troubleshooting PPP ... B:7-53
 - debug commands ... B:7-54
- PPTP
 - ALG for ... A:4-20
- preshared key
 - adding to VPN remote ID list ... A:10-32
 - for VPN ... A:10-10
 - viewing VPN ... A:10-71
- Privacy Enhanced Mail ... A:10-59, A:10-61
- probe ... A:9-3, A:9-11
 - See also* network monitor probe
- ProCurve Secure Router
 - models ... B:1-5
- product documentation ... B:1-7, A:1-6
- Protocol Independent Multicast-Sparse Mode
 - See* PIM-SM
- PSTN ... B:4-4, B:5-4
- PTT authorities ... B:4-3, B:5-3

- public carrier
 - central office of ... B:4-4, B:5-4, A:3-7
 - See also* local loop
- public key infrastructure
 - See* PKI
- public switched telephone network ... B:4-4, B:5-4
- Public Telephone and Telegraph authorities ... B:4-3, B:5-3
- PVC
 - ATM ... B:7-18
 - Frame Relay subinterface for ... B:6-28

Q

- Q.931 ... B:8-11
- QoS
 - CBWFQ ... A:8-11, A:8-19
 - configuration wizard ... A:16-62
 - configuring with Web browser interface ... A:16-58
 - data packets ... A:8-4
 - Ethernet ... A:8-58
 - example configuration ... A:8-61
 - FIFO ... A:8-10
 - Frame Relay ... A:8-53
 - example configuration ... A:8-57
 - rate limiting ... A:8-54
 - FRF.12 ... A:8-12, A:8-53
 - high-priority traffic ... A:8-4
 - LLQ ... A:8-11, A:8-32
 - maps
 - See* QoS map
 - match command
 - dscp ... A:8-38
 - ip rtp ... A:8-26
 - list ... A:8-38
 - precedence ... A:8-38
 - mechanisms ... A:8-5
 - monitoring ... A:8-68
 - managing queues ... A:8-70
 - QoS maps ... A:8-69
 - OSPF ... A:8-5
 - SIP ... A:8-62
 - Telnet ... A:8-4
 - ToS field ... A:8-6
 - DiffServ ... A:8-7
 - IP precedence ... A:8-6
 - PHBs ... A:8-8
 - ToS marking ... A:8-45

- VoIP ... A:8-4
- WFQ ... A:8-11, A:8-14
- QoS map ... A:8-12, A:8-13
 - configuring ... A:8-21, A:8-45
 - deleting ... A:8-70
 - entry order ... A:8-12
 - forced inactive ... A:8-71
 - match command ... A:8-74
 - dscp ... A:8-46, A:8-64
 - ip rtp ... A:8-39, A:8-49, A:8-65
 - list ... A:8-41, A:8-48, A:8-67, A:8-74
 - precedence ... A:8-46
 - protocol bridge ... A:8-26, A:8-42, A:8-50, A:8-74
 - ToS marking ... A:8-13
 - viewing ... A:8-69

- queue
 - monitoring ... A:8-70
 - subqueue ... A:8-14, A:8-16, A:8-70
- queuing
 - low-latency
 - See* LLQ ... A:8-6
 - weighted fair
 - See* WFQ

R

- R interface ... B:8-9, A:3-9
- RADIUS server
 - authentication ... B:2-19
 - configuring through Web browser interface ... B:14-36
 - defining ... B:2-31
 - defining group ... B:2-33
 - global settings ... B:2-34
 - troubleshooting ... B:2-40
 - Xauth with ... A:10-51, A:10-52
- RAM ... B:1-29
- rapid spanning tree protocol
 - See* RSTP
- rate limiting
 - Ethernet ... A:8-58, A:8-72
 - Frame Relay ... A:8-53, A:8-54, A:8-67
- RBE ... B:7-40
 - configuring ... B:7-41
 - example environment ... B:7-41
- READSL ... B:7-4, B:7-6

- real-time transport protocol
 - See* RTP
- rebooting router
 - with Web browser interface ... B:14-20
- redundant power source ... B:1-29
- reflexive traffic ... A:4-10, A:4-12
 - attack check ... A:4-16
 - illustration of ... A:4-12, A:4-17
- reload command ... A:5-38
- reload in command ... B:1-73
- rendezvous point
 - See* RP
- repeater ... B:5-6
 - carrier line ... B:4-6
 - ISDN connection ... B:8-7, A:3-7
- resource pool ... A:3-28
 - assigning ISDN group ... B:8-45
 - configuring through Web browser interface ... B:14-100
 - for demand interface ... B:8-30
 - viewing ... B:8-68, A:3-80
- RIP
 - advertising a network ... B:15-21
 - advertising a non-RIP network ... B:15-23
 - as an interior gateway protocol ... B:15-7
 - compared to OSPF and BGP ... B:15-9
 - compatibility between versions ... B:15-14, B:15-153
 - configuration options ... B:15-18
 - configuring with Web browser interface ... A:16-146
 - default administrative distance ... B:15-11
 - default intervals ... B:15-18
 - overview ... B:15-12
 - passive interface ... B:15-30
 - poison reverse ... B:15-15, B:15-17
 - redistributing routes
 - connected ... B:15-23
 - OSPF ... B:15-24
 - static ... B:15-24
 - route filtering ... B:15-24
 - route summarization ... B:15-27
 - split horizon ... B:15-15, B:15-17
 - timing intervals ... B:15-17
 - triggered updates ... B:15-15, B:15-17
 - troubleshooting ... B:15-153
 - updates ... B:15-15
 - version ... B:15-13
 - version for an interface ... B:15-20
 - version, configuring ... B:15-20
- RJ-11 connector ... B:7-12, B:8-8
- RJ-45 connector ... B:3-2, B:8-8
- RJ-48C connector ... B:4-7, B:9-14
- route maps
 - applying policies to inbound routes ... B:15-104
 - applying to neighbor ... B:15-106
 - controlling routes advertised ... B:15-92
 - controlling routes neighbor advertises ... B:15-97
 - creating ... B:15-88
 - deleting communities from ... B:15-105
 - entry in ... B:15-90
 - filtering inbound routes ... B:15-103
 - filtering routes
 - AS path ... B:15-95
 - community ... B:15-94
 - network address ... B:15-92
 - load balancing ... B:15-99, B:15-100
- routed bridged encapsulation
 - See* RBE
- router management
 - configuration files ... B:1-30, B:1-33
 - contexts ... B:1-35
 - controlling access ... B:2-4
 - rebooting using reload ... B:1-51
 - remote access ... B:2-7
 - saving changes ... B:1-33
 - software updates ... B:1-8
- routing
 - administrative distances ... B:15-11
 - advantages of routing protocols ... B:15-10
 - clearing routes ... B:11-28, B:15-151
 - comparing routing protocols ... B:15-9
 - configuring through Web browser interface ... B:14-119
 - disadvantages of routing protocols ... B:15-10
 - dynamic ... B:11-10
 - Layer 2 devices with ... A:14-2
 - floating static route ... B:11-16
 - monitoring routes with traceroute ... B:11-27
 - monitoring static routes ... A:9-6, A:9-31, A:9-42
 - network monitoring with tracks ... B:11-16
 - non-IP traffic ... B:10-4
 - RIP updates ... B:15-15
 - See also* PBR
 - static
 - See* static route

- tunneling updates ... A:10-14, A:11-8, B:15-23, B:15-154
- updates
 - BGP ... B:15-72, B:15-165
 - OSPF ... B:15-42, B:15-59
- Routing Information Protocol
 - See* RIP
- routing table
 - information included in ... B:11-7, B:11-9
 - matching packet to route ... B:11-7
 - multicast
 - See* multicast routing table
 - OSPF ... B:15-159
 - viewing ... B:11-24, B:11-25, B:15-148, B:15-149
 - with routing protocols ... B:15-7
- routing, dynamic routing
 - See* RIP, OSPF, and BGP
- RP ... A:13-3, A:13-6
 - RP set ... A:13-17
 - selecting ... A:13-17, A:13-30, A:13-62
 - set
 - See* RP set
 - SP tree, joining ... A:13-10, A:13-26, A:13-35, A:13-50
 - static ... A:13-17, A:13-18
 - supporting all groups ... A:13-31
 - supporting specific groups only ... A:13-32
- RP set
 - configuring ... A:13-32, A:13-67
 - troubleshooting ... A:13-62
- RPF check, disabling for network monitoring ... A:9-40
- RPS ... B:1-29
- RSTP
 - BPDU ... B:10-12
 - BPDU guard ... B:10-21
 - compatibility with STP ... B:10-17
 - configuration tasks ... B:10-11, B:10-17
 - connection type ... B:10-15, B:10-21
 - disabling ... B:10-23
 - edge port ... B:10-15, B:10-19
 - improvements over STP ... B:10-14
 - link cost ... B:10-18, B:10-29
 - overview ... B:10-4
 - priority for becoming root ... B:10-18
 - sync ... B:10-15
 - timers ... B:10-22
 - troubleshooting ... B:10-25, B:10-26

- valid interfaces ... B:10-11
- viewing the spanning tree ... B:10-26, B:10-27
- RTP ... A:8-26, A:8-35, A:8-39, A:8-49
 - compression ... A:8-35
 - cRTP ... A:8-35
- running-config ... B:1-30

S

- S interface ... B:8-8, A:3-9
- SA ... A:10-7
 - See also* IKE SA and IPSec SA
- SafeMode ... B:1-62
- SAPI ... B:8-10
- saving changes ... B:1-57
- SCEP ... A:10-56, A:10-57
- secure copy server
 - enabling ... B:2-14
 - enabling through Web browser interface ... B:14-22, A:16-20
- secure router operating system
 - See* SROS
- security
 - AAA subsystem ... B:2-15
 - accounting ... B:2-27
 - ACL ... A:5-6
 - ACP ... A:5-26
 - authorization ... B:2-24
 - console password ... B:2-5
 - enable mode password ... B:2-4
 - encrypting passwords ... B:2-13
 - local user lists ... B:2-11
 - management access ... B:2-4
 - RADIUS server ... B:2-31
 - remote access ... B:2-7
 - show users ... B:2-14
 - TACACS+ server ... B:2-35
 - Telnet password ... B:2-8
- security parameter index
 - See* SPI
- self certificate
 - definition ... A:10-56
 - importing manually ... A:10-61
 - requesting ... A:10-59
- serial interface
 - accessing ... B:5-12
 - activating ... B:5-14

- binding
 - to Frame Relay interface ... B:6-37
 - to HDLC interface ... B:6-44
 - to PPP interface ... B:6-11
 - clock source ... B:5-13
 - configuring ... B:5-12
 - configuring through Web browser interface ... B:14-59
 - Data Link Layer
 - Frame Relay ... B:6-23
 - HDLC ... B:6-40
 - PPP ... B:6-6
 - rxclock, inverting ... B:5-14
 - serial-mode setting ... B:5-12
 - troubleshooting ... B:5-18
 - problem with line going down ... B:5-21
 - solutions to problems ... B:5-20
 - txclock, inverting ... B:5-13
 - viewing configuration of ... B:5-16
 - serial module
 - cable shipped with ... B:5-8
 - connecting to CSU/DSU ... B:5-8
 - for E1-carrier lines ... B:5-3
 - for T1-carrier line ... B:5-3
 - port number ... B:5-12
 - slot number ... B:5-12
 - standards supported ... B:5-7
 - used with external CSU/DSU ... B:5-7
 - service access point identifier ... B:8-10
 - Service Level Agreement ... B:6-19
 - service level agreement
 - and EIR ... B:6-35
 - session initiation protocol
 - See* SIP
 - SHDSL ... B:7-4
 - show command ... A:8-69
 - basic mode context ... B:1-41
 - bridge table ... B:10-8
 - crypto ike ... A:10-72
 - crypto ipsec ... A:10-72
 - crypto map ... A:10-72
 - DHCP client binding table ... B:13-19
 - DHCP lease on router interface ... B:13-28
 - enable mode commands ... B:1-51
 - event-history ... A:4-26
 - for content filtering ... A:7-12
 - Frame Relay ... A:2-14
 - interfaces
 - ADSL ... B:7-42
 - ATM ... B:7-45
 - BRI ... B:8-65, A:3-73
 - demand ... B:8-61, A:3-77
 - DSX-1 ... B:9-20
 - E1 ... B:4-28, B:9-5
 - E1 for G.703 ... B:9-13
 - Ethernet ... B:3-20
 - G.703 ... B:9-10
 - modem ... A:3-76
 - T1 ... B:4-28
 - T1 for DSX-1 ... B:9-20
 - tunnel ... A:11-13
 - ip access-lists ... A:10-72
 - LLDP activity ... A:14-8
 - LLDP neighbors ... A:14-6, A:14-7
 - LLDP neighbors, real time ... A:14-8
 - LLDP timers ... A:14-11
 - logical interfaces ... B:6-54
 - persistent backup ... A:3-87
 - PPPoE ... B:7-52
 - probe ... A:9-56
 - qos map ... A:8-69
 - qos map interface ... A:8-69
 - queue ... A:8-70
 - routing table ... B:11-24
 - running-config
 - DSX-1 ... B:9-21
 - G.703 ... B:9-11
 - show connections ... B:5-17
 - show tech ... B:1-58, A:1-21
 - SNMP ... B:2-64
 - spanning tree ... B:10-26
 - track ... A:9-55
 - verbose option ... B:1-55
- showtime
 - for ADSL ... B:7-13
 - monitor for ADSL ... B:7-16
 - signaling
 - electrical, for WAN connection ... B:4-3
 - Simple Certificate Enrollment Protocol ... A:10-56, A:10-57
 - SIP ... A:8-52, A:8-62, A:8-64
 - ALG for ... A:4-19
 - configuring ... A:8-63
 - definition ... A:8-62
 - destination port ... A:8-66
 - enabling, services ... A:8-62

- site-to-site VPN
 - IKE mode for ... A:10-27
 - peer ID in crypto map ... A:10-43
 - peer ID in IKE policy ... A:10-24
 - peer ID in remote ID list ... A:10-33
 - specifying traffic for ... A:10-37
 - Xauth with ... A:10-49
- SLA ... B:6-19
 - and EIR ... B:6-35
- slot
 - narrow ... B:1-15
 - supported modules ... B:1-16
 - wide ... B:1-20
- slot number
 - for ADSL interfaces ... B:7-12
 - for backup BRI interfaces ... A:3-38, A:3-49
 - for backup modem interfaces ... A:3-38
 - for BRI interfaces ... B:8-40
 - for E1 interfaces ... B:4-11
 - for Ethernet interfaces ... B:3-3
 - for serial interface ... B:5-12
 - for T1 interfaces ... B:4-11
- smart jack ... B:4-5
 - for ISDN ... A:3-8
- Smurf attack ... A:4-9
- SNMP ... A:14-2
 - agent, enabling on router ... B:2-47
 - architecture ... B:2-44
 - communities ... B:2-54
 - configuring through Web browser interface ... B:14-42
 - engine ID
 - local ... B:2-51
 - remote ... B:2-52
 - group, configuring ... B:2-56
 - identity information ... B:2-48
 - informs ... B:2-62
 - retry attempts ... B:2-62
 - wait time ... B:2-62
 - manager contact for router ... B:2-49
 - router location ... B:2-48
 - source interface ... B:2-63
 - support in router ... B:2-47
 - trap receiver (host) ... B:2-61
 - traps ... B:2-60
 - URL for Web browser interface ... B:2-50
 - user, configuring ... B:2-58
 - versions ... B:2-45
 - viewing neighbors' management agent ... A:14-6
 - views
 - configuring ... B:2-54
 - definition ... B:2-52
- SNR-margin ... B:7-15
 - monitoring ... B:7-16
- SNTP
 - client ... B:1-86
 - server ... B:1-86
 - source address for ... B:1-87
 - troubleshooting ... B:1-88
 - viewing, settings ... B:1-88
- software
 - downloading updates ... B:1-8, A:1-7
 - transfer ... B:1-78
 - transfer using
 - compact flash ... B:1-83
 - TFTP ... B:1-80
- spanning tree protocol
 - See* RSTP
 - See* STP
- speed
 - Ethernet connection settings ... B:3-11
- SPI
 - displaying ... A:10-71
 - manually setting ... A:10-67, A:10-68
 - matching packets to VPN tunnel ... A:10-22
 - role in IPSec SA ... A:10-7
- SPID
 - demand routing ... A:3-41
 - persistent backup connection ... A:3-51
 - troubleshooting problems with ... A:3-75
- spoofing
 - demand interface ... A:3-23
- SROS
 - and AutoSynch™ technology ... B:1-34
 - basic mode ... B:1-36
 - boot code ... B:1-30
 - enable mode ... B:1-36
 - global configuration mode ... B:1-37
 - hierarchy ... B:1-34
 - managing with Web browser interface ... A:16-11
 - software ... B:1-30
 - version
 - viewing neighbors' ... A:14-5

SSH

- configuring password through Web browser interface ... B:14-27, B:14-32
- enabling through Web browser interface ... B:14-22, A:16-20
- lines ... B:2-12
- local user list ... B:2-11
- startup-config ... B:1-30
- static route ... B:11-9
 - advantages and disadvantages of ... B:11-10
 - applications ... B:11-13
 - configuring ... B:11-13, B:11-14, B:11-15
 - configuring through Web browser interface ... B:14-103, B:14-117
 - deleting ... B:11-29, B:15-152
 - floating ... B:11-16
 - demand routing ... A:3-43
 - persistent backup connections ... A:3-69
 - for demand interface ... B:8-46
 - monitoring ... A:9-6, A:9-31, A:9-42
 - null interface, through ... B:11-18
 - redistributing ... B:15-59
 - redistributing through RIP ... B:15-24
 - troubleshooting ... B:11-24
- stealth mode ... A:4-17
- STP
 - BPDU ... B:10-12
 - configuration tasks ... B:10-11, B:10-23
 - configuring through Web browser interface ... B:14-112
 - disabling ... B:10-23
 - link cost ... B:10-18, B:10-29
 - overview ... B:10-4
 - priority for becoming root ... B:10-18
 - states ... B:10-13
 - timers ... B:10-22
 - troubleshooting ... B:10-25, B:10-26
 - valid interfaces ... B:10-11
 - viewing the spanning tree ... B:10-26, B:10-27
- subinterface
 - ATM ... B:7-18, A:8-17
 - Ethernet ... B:3-19
 - Frame Relay ... B:6-28, A:8-56
- Syndrop attack ... A:4-9
- SYN-flood
 - attack ... A:4-9, A:4-10
 - attack check ... A:4-16
- syslog server
 - forwarding logs to ... A:4-28

T

- T interface ... B:8-8, A:3-9
 - T1 + DSX-1
 - See* DSX-1 interface and drop-and-insert module ... B:9-14
 - T1 interface
 - activating ... B:4-21
 - binding
 - to Frame Relay interface ... B:6-37
 - to HDLC interface ... B:6-44
 - to PPP interface ... B:6-11
 - channels for ... B:4-14
 - clock source ... B:4-18
 - configuration mode context for ... B:4-11
 - configuring through CLI ... B:4-10
 - configuring through Web browser interface ... B:14-54
 - Data Link Layer
 - Frame Relay ... B:6-23
 - HDLC ... B:6-40
 - PPP ... B:6-6
 - FDL channel ... B:4-20
 - frame format ... B:4-17
 - interface range command ... B:4-12
 - LBO ... B:4-19
 - line coding ... B:4-15
 - line errors ... B:4-23
 - port number ... B:4-11
 - slot number ... B:4-11
 - speed for channel ... B:4-15
 - threshold commands ... B:4-23
 - troubleshooting ... B:4-31
 - viewing configuration of ... B:4-29
 - viewing status of ... B:4-27
- T1 module
 - standards supported ... B:4-9
 - with built-in CSU/DSU ... B:4-9
- T1-carrier line
 - 1.544 Mbps bandwidth ... B:4-3
 - 24 channels ... B:4-13
 - analog voice on ... B:4-3
 - CSU/DSU in router ... B:4-7
 - elements of ... B:4-3
 - external CSU/DSU ... B:4-6
 - for analog voice ... B:9-3
 - local loop ... B:4-4
 - serial interface for ... B:5-3
 - with DSX-1 interface ... B:9-3

- TA ... B:8-7, A:3-8
- TACACS+ server
 - authorization ... B:2-24
 - clear statistics ... B:2-42
 - defining ... B:2-35
 - global settings ... B:2-38
 - group of ... B:2-37
 - troubleshooting ... B:2-41
 - Xauth with ... A:10-51, A:10-52
- Targa attack ... A:4-9
- TCP
 - attacks ... A:4-10
 - session timeout ... A:4-21, A:4-22
- TCP connect probe ... A:9-11, A:9-20
 - See also* network monitor probe
- TDM
 - used in carrier lines ... B:4-13
- TE1 ... B:8-7, A:3-8
- TE2 ... B:8-7, A:3-8
- TearDrop attack ... A:4-9
- TEI ... B:8-10
- Telnet ... A:5-21
 - ACL to control access ... A:5-23
 - configuring access to ... B:2-8
 - configuring password through Web browser interface ... B:14-29
 - enabling through Web browser interface ... B:14-22, A:16-20
 - password for ... B:2-8
 - QoS ... A:8-4, A:8-41
 - using local user list for access ... B:2-13
- terminal adapter ... B:8-7, A:3-8
- terminal endpoint identifier ... B:8-10
- terminal equipment 1 ... B:8-7, A:3-8
- terminal equipment 2 ... B:8-7, A:3-8
- TFTP
 - file transfer with ... B:1-80
 - server, specifying in DHCP pool ... B:13-11
 - support, enabling through Web browser interface ... B:14-22, A:16-20
- threshold
 - E1 ... B:4-22
 - T1 ... B:4-22
- time division multiplexing ... B:4-13
- timeout
 - application ... A:4-22
 - protocol ... A:4-21
 - session ... A:4-21
- timers
 - LLDP
 - setting ... A:14-14
 - viewing ... A:14-11
- ToS ... A:8-5, A:8-6, A:8-7, A:8-38
 - assured forwarding ... A:8-9
 - bits ... A:8-7
 - CBWFQ ... A:8-20
 - classifying traffic ... A:8-21
 - definition ... A:8-6
 - DiffServ ... A:8-7, A:8-9
 - IP precedence ... A:8-6, A:8-8
 - LLQ ... A:8-37, A:8-44, A:8-75
 - marking ... A:8-45, A:8-46, A:8-50, A:8-64
 - values ... A:8-8, A:8-9, A:8-21, A:8-38
 - viewing ... A:8-69
 - VoIP ... A:8-49
 - WFQ ... A:8-11
- traceroute command ... B:1-36, B:11-27
- track ... A:9-5, A:9-26
 - attaching to DHCP client for network monitoring ... B:13-26
 - See also* network monitor track
- traffic
 - filtering with ACL ... A:5-6
 - filtering with ACP ... A:5-26
 - interesting, for backup with demand routing ... A:3-24
- traffic shaping
 - Ethernet ... A:8-58, A:8-72, A:8-78
 - Frame Relay ... A:8-55, A:8-57, A:8-67
 - See also* rate limiting
- training phase, ADSL ... B:7-13
- training-monitor, for ADSL ... B:7-16
- transform set
 - algorithms, specifying ... A:10-40
 - tunnel mode ... A:10-42
 - viewing ... A:10-71, A:10-86
- transmission media ... B:4-3
- trap receiver, SNMP ... B:2-61
- traps, SNMP ... B:2-60

troubleshooting

- AAA subsystem ... B:2-39
- ACL ... A:5-56
- ACL for demand routing ... B:8-73, A:3-82
- ACP ... A:5-56
- ADSL interface ... B:7-47
- ATM interface ... B:7-49
- ATM subinterface ... B:7-50
- AutoSynch™ ... B:1-71
- BGP ... B:15-164
- BRI backup interfaces ... A:3-72
- bridging ... B:10-10
- CHAP ... B:6-65
- compact flash performance ... B:1-71
- debug commands ... B:1-49
- debug isdn commands ... B:8-73, A:3-83
- demand routing ... B:8-70, A:3-81
- DHCP client ... B:13-28
- DHCP server ... B:13-19
- DNS ... B:12-11
- DSX-1 interface ... B:9-21
- E1 interface ... B:4-31
- Ethernet interface ... B:3-25
- events command ... B:1-51
- firewall ... A:4-13, A:4-26, A:4-29
- Frame Relay interface ... B:6-66
- G.703 interface ... B:9-12
- GRE ... A:11-13
- HDLC interface ... B:6-70
- IKE ... A:10-76
- IPSec ... A:10-73
- MLFR ... A:2-16
- MLPPP ... A:2-15
- multilinks ... A:2-12
- network monitoring ... A:9-58
- OSPF ... B:15-155
- persistent backup connection ... A:3-92
- PIM-SM ... A:13-48, A:13-56
- PPP authentication ... B:6-63
- PPP interface ... B:6-59
- PPPoE ... B:7-51
- QoS ... A:8-71
- RADIUS server ... B:2-40
- RIP ... B:15-153
- routing ... B:15-148

- serial interface ... B:5-18
- static routing ... B:11-24
- T1 interface ... B:4-31
- TACACS+ server ... B:2-41
- tunnel ... A:11-13
- VPN ... A:10-73
- with reload in command ... B:1-73

TS16

- configuring ... B:9-9
- description ... B:9-9

tunnel ... A:10-4, A:11-4

- configuring with Web browser interface ... A:16-136
- destination ... A:11-4, A:11-5, A:11-6, A:11-8
- IP address ... A:11-4, A:11-7
- key ... A:11-7
- multicast ... A:12-17
- See also* VPN tunnel
- source ... A:11-4, A:11-5
- troubleshooting ... A:11-13

Twinge attack ... A:4-9

type of service

See ToS

U

U interface ... B:8-8, A:3-9

UDP

- forwarding DHCP ... B:13-32
- session timeout ... A:4-21, A:4-22

UNI

for Frame Relay ... B:6-21

unnumbered interface

- ATM subinterface as ... B:7-25
- Ethernet interface as ... B:3-10
- Frame Relay subinterface as ... B:6-33
- HDLC interface as ... B:6-43
- PPP interface as ... B:6-9

updating

- boot code ... B:1-60

users

- SNMP ... B:2-58
- viewing, accessing router ... B:2-14

user-to-network interfaces

- Frame Relay ... B:6-21

V

- V.35 cable ... B:5-9
 - VCI ... B:7-19
 - VDSL ... B:7-4
 - See also* ADSL
 - verbose option
 - for show commands ... B:1-55
 - videoconferencing
 - ALG for ... A:4-19
 - virtual channel identifier ... B:7-18
 - virtual path identifier ... B:7-18
 - virtual private network
 - See* VPN
 - virtual routing and forwarding
 - used by ISP ... B:15-69
 - VLAN
 - DHCP scopes ... B:13-5, B:13-15, B:13-16
 - enabling support for ... B:3-18
 - ID for Ethernet subinterface ... B:3-19
 - IP address for Ethernet subinterface ... B:3-20
 - routing, traffic ... B:3-17
 - support for ... B:3-16
 - tagging ... B:3-16
 - VLAN trunking
 - See* VLAN, tagging
 - VoIP
 - ALG for ... A:4-19
 - bandwidth for ... A:8-32, A:8-33
 - packets ... A:8-34
 - QoS ... A:8-4
 - example configuration ... A:8-61
 - Frame Relay ... A:8-53
 - LLQ ... A:8-39
 - packet marking ... A:8-49, A:8-66
 - signaling traffic ... A:8-47, A:8-66
 - VPI ... B:7-19
 - VPN
 - applying crypto map to interface ... A:10-46
 - client-to-site ... A:10-4
 - configuration
 - overview ... A:10-15
 - tasks ... A:10-23
 - with Web browser interface ... A:16-89
 - wizard ... A:16-89
 - GRE tunnel ... A:10-13
 - IPSec module for ... A:10-14
 - module ... B:1-27, A:10-23
 - monitoring ... A:10-70
 - multiple sites ... A:10-45
 - peer
 - See* VPN peer
 - See also* client-to-site VPN, crypto map, IKE, IP Security (IPSec), site-to-site VPN
 - site-to-site ... A:10-4
 - traffic
 - defining in a crypto map ... A:10-45
 - defining in an ACL ... A:10-35, A:10-37
 - example configuration ... A:10-39
 - restricting hosts ... A:10-36
 - troubleshooting ... A:10-73
 - comparing policies ... A:10-80, A:10-84
 - debugging IKE ... A:10-82
 - permitting all traffic ... A:10-75
 - returning policies to defaults ... A:10-86
 - tunnel ... A:10-4
 - VPN peer
 - adding to remote ID list ... A:10-32
 - associating with IPSec policies ... A:10-35
 - dynamic peer
 - IKE initiate mode with ... A:10-27
 - peer ID in crypto map ... A:10-44
 - peer ID in IKE policy ... A:10-25
 - ID
 - specifying ... A:10-17
 - types ... A:10-18, A:10-33
 - with IKE main mode ... A:10-34
 - mobile users
 - peer ID in crypto map ... A:10-44
 - peer ID in IKE policy ... A:10-26
 - problems with IKE main mode ... A:10-28
 - See also* IKE mode config and Xauth
 - static peer
 - peer ID in crypto map ... A:10-43
 - peer ID in IKE policy ... A:10-24
 - viewing remote ID list ... A:10-71
- VPN tunnel ... A:10-4, A:10-7
 - See also* IP Security (IPSec)

W

WAN connection

- dedicated ... B:4-3
- elements of ... B:4-3, B:5-3
- view active ... B:5-17

Web browser interface ... B:1-5, B:1-10

- AAA subsystem ... B:14-35
- accessing ... B:1-11, A:1-10
- ACLs ... A:16-41
- ACPs ... A:16-44
- ADSL interface ... B:14-78
- ATM interface ... B:14-80
- AutoSynch™ ... B:14-8, A:16-7
- BRI interface ... B:14-90
- bridging ... B:14-108
- certificates ... A:16-123
- connect sequence ... B:14-98
- debug ... B:14-15, A:16-14
- default route ... B:14-119
- demand interface ... B:14-95
- description ... A:1-9
- DHCP ... B:14-126
- DNS server ... B:14-121
- DSX-1 interface ... B:14-105
- E1 interface ... B:14-54
- enable mode password ... B:14-28
- enabling access to ... B:14-5, A:16-4
- enabling IP services ... B:14-22, A:16-20
- Ethernet interface ... B:14-40
- file management ... B:14-9, A:16-8
- firewall ... A:16-27
- firewall wizard ... A:16-37
- Frame Relay interface ... B:14-68
- G.703 interface ... B:14-105
- HDLC interface ... B:14-74
- ISDN group ... B:14-93
- ISDN modules ... B:14-88
- LLDP ... A:16-141
- logging ... A:16-30
- managing Secure Router OS ... B:14-12
- MLFR ... A:16-26
- MLPPP ... A:16-24
- network monitoring ... A:16-75
- organization of ... B:1-12, A:1-11

- OSPF ... A:16-148
- passwords ... B:14-27
- PPP authentication ... B:14-65
- PPP interface ... B:14-62
- QoS ... A:16-58
- QoS wizard ... A:16-62
- RADIUS server ... B:14-36
- resource pool ... B:14-100
- RIP ... A:16-146
- Secure Router OS, managing ... A:16-11
- serial module ... B:14-59
- SNMP ... B:14-42
- spanning tree protocol ... B:14-112
- static route ... B:14-103, B:14-117
- T1 ... B:14-54
- TACACS+ server ... B:14-38
- tunnels ... A:16-136
- VPN wizard ... A:16-89

weighted fair queuing

See WFQ

WFQ ... A:8-11, A:8-14

- conversation subqueue ... A:8-11, A:8-14, A:8-15
 - packet threshold ... A:8-18, A:8-70
- enabling ... A:8-17
- queue size ... A:8-18
- shortcomings ... A:8-15, A:8-16, A:8-23, A:8-49, A:8-71
- weight ... A:8-15

wildcard bits

- ACL for NAT ... A:6-10
- in ACL ... B:8-20, A:5-10

WinNuke

- attack ... A:4-10, A:4-11
- optional firewall check ... A:4-15

WINS server

- DHCP pool, in ... B:13-11
- in IKE mode config pool ... A:10-48

wizard

- firewall ... A:16-37
- network monitoring ... A:16-75
- QoS ... A:16-62
- VPN ... A:16-89

X

X.21 cable ... B:5-10

Xauth

host

configuration tasks ... A:10-53

generic authentication ... A:10-53

OTP authentication ... A:10-54

RADIUS authentication ... A:10-53

server

configuration tasks ... A:10-50

enabling ... A:10-52

local username database for ... A:10-50

RADIUS database for ... A:10-51

TACACS+ database for ... A:10-51